

Code: KONW/UNICAB+TWIN-INV

## TV-SAT LNB KONW/UNICAB+TWIN-INV

Net: 39.77 EUR Gross: 48.92 EUR

The KONW/UNICAB+TWIN-INV LNB is equipped with 3 outputs: UNICABLE for connecting max. 4 sat-receivers using single coaxial cable and for signal separation on any satellite splitters, and 2x SINGLE FULLBAND for connecting standard sat-receiver.

All sat-receivers operate fully independently. The condition is to have implemented the UNICABLE function, which based on using 4 frequencies for signal transmission: 1 - 1680 MHz, 2 - 1420 MHz, 3 - 2040 MHz, 4 - 1210 MHz.



### SPECIFICATION

Type:	TWIN + UNICABLE
Input frequency:	<ul style="list-style-type: none"><li>• 10.7 GHz ... 11.7 GHz</li><li>• 11.7 GHz ... 12.75 GHz</li></ul>
Output frequency:	<ul style="list-style-type: none"><li>• UNICABLE output : 1210 MHz, 1420 MHz, 1680 MHz, 2040 MHz</li><li>• 2 x SINGLE FULLBAND output : 950 ... 1950 MHz, 1100 ... 2150 MHz</li></ul>
Oscillator frequency:	9.75 GHz / 10.6 GHz
Number of outputs:	2 pcs F socket - SINGLE FULLBAND output , 1 pcs F socket - UNICABLE output
Gain :	min. 55 dB
S/N ratio:	0.2 dB
Output impedance:	75 Ω
LNB switch:	DiSEqC
H/V polarization switching:	13 / 18 V
Band switching:	22 kHz
Recommended dish diameter:	75 - 90 cm
Neck diameter:	40 mm
Main features:	<ul style="list-style-type: none"><li>• Independently operation connected in series sat-receivers due to UNICABLE technology</li><li>• Modern technology eliminates the need for starry wiring</li><li>• Very low phase noise (LNB recommended for 8PSK HDTV)</li><li>• The ideal solution in situations where there is only one cable placed from the antenna installation site to home</li></ul>
Weight:	0.310 kg
Dimensions:	145 x 118 x 60 mm
Manufacturer / Brand:	INVERTO
Guarantee:	2 years

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

## PRESENTATION





Dimensions:

