

Code: SMS-5/12

MULTISWITCH **SMS-5/12** 5 INPUTS / 12 OUTPUTS SIGNAL

Net: **60.55 EUR** Gross: **74.48 EUR**



SPECIFICATION

Inputs:	4 x 950 MHz ... 2150 MHz , 1 x 47 MHz ... 790 MHz
Outputs:	12 x 47 ... 2150 MHz
TV amplification (cable pre-correction):	2 dB
SAT amplification (cable pre-correction):	2 dB
Isolation:	<ul style="list-style-type: none">• Interpolarized H/V : 28 dB• Between inputs TV/SAT : 28 dB• Between inputs SAT/SAT : 30 dB• Outputs : 30 dB
Return loss:	TV input : 10 dB SAT input : 11 dB Outputs : 10 dB
Maximal output level SAT:	101 dB μ V (EN50083-3)
Maximal output level TV:	85 dB μ V (EN50083-5)
Switching signals:	13 V / 18 V 0, 22 kHz
LNB power supply:	max. 600 mA
Pre-amplifiers powering:	12 V DC
Power supply:	90 ... 240 V AC/50Hz
Weight:	1.024 kg
Dimensions:	465 x 120 x 70 mm
Manufacturer / Brand:	SIGNAL
Guarantee:	2 years

PRESENTATION

Device connectors:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

