

Code: TMS-9/12S

MULTISWITCH **TMS-9/12S** 9 INPUTS / 12 OUTPUTS TRIAX

Net: **114.66 EUR** Gross: **114.66 EUR**



SPECIFICATION


Inputs:	• 1 x 47 MHz ... 694 MHz - Active / 5 MHz ... 862 MHz - Passive, • 8 x 950 MHz ... 2200 MHz
Outputs:	12 x 47 ... 2200 MHz
TV amplification (cable pre-correction):	0 dB
SAT amplification (cable pre-correction):	-3 ... 2 dB
Isolation:	• Interpolarized H/V : 30 dB • Between inputs SAT/TV : 30 dB • Outputs : 30 dB - SAT • Outputs : 25 dB - TV
Return loss:	TV input : > 10 dB SAT input : > 10 dB Outputs : > 10 dB
Maximal output level SAT:	100 dB μ V (-35dB IMD3)
Maximal output level TV:	90 dB μ V (-60dB IMD3)
Switching signals:	13 V / 18 V, 0 / 22 kHz, DiSEqC 1.0, DiSEqC 2.0
LNB power supply:	max. 1000 mA
Pre-amplifiers powering:	—
Power supply:	180 ... 264 V AC
Weight:	0.9 kg
Dimensions:	270 x 142 x 64 mm
Manufacturer / Brand:	TRIAX
Guarantee:	6 years

PRESENTATION

Top view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Device connectors:





In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------