

Code: MOD/SIG-400/DVB-T

## MODULATOR DVB-T MOD/SIG-400/DVB-T

Net: 145.31 EUR Gross: 178.73 EUR



The MOD/SIG-400/DVB-T digital modulator allows to put the HD signal (from camera, terrestrial, satellite TV receiver, Blu-ray, DVD player, etc.) from HDMI input to RF OUT output as DVB-T (COFDM), Full HD 1080p standard in VHF/UHF bands.

### SPECIFICATION

Inputs:	1 pcs HDMI, Full HD 1080p , 1 pcs RF (F)
Encoding:	H.264 MP@L 3.0/3.1/4.0
Supported HDMI resolutions:	480i @ 59.94 / 60 fps 576i @ 50 fps 720p @ 50 / 59.94 / 60 fps 1080i @ 50 / 59.94 / 60 fps 1080p @ 59.94 / 60 fps
Output:	1 pcs RF (F)
Insertion loss WE-WY VHF/UHF:	10 ... 12 dB
RF output level adjustment:	80 ... 93 dB $\mu$ V
RF output frequency (channels) range:	142.5 ... 858 MHz
Modulation type:	QPSK, 16-QAM, 64-QAM
Power supply:	12 V DC / 2 A (power adapter included)
Main features:	<ul style="list-style-type: none"><li>• Firmware upgrade via USB cable</li><li>• Aspect ratios 4:3, 16:9</li><li>• MER &gt; 31 dB</li></ul>
Weight:	0.41 kg
Dimensions:	173 x 122 x 53 mm
Guarantee:	2 years

### PRESENTATION

Front panel:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Device connectors:



In the kit:

