

Code: VMT-215-S

## MONITOR HDMI, VGA, CVBS **VMT-215-S** 21.5 " VILUX

Net: **80.76 EUR** Gross: **99.33 EUR**

Monitor is equipped with plastic housing. It has two types of mounting. As standalone or VESA 75 mounting.

The device is designed to continuous work in closed spaces.



### SPECIFICATION

Screen size:	21.5 "
Native resolution:	1920 x 1080 px
Aspect ratios:	16 : 9
Matrix type:	TFT-LCD color matrix
Matrix backlight:	In LED technology
Contrast:	1000 : 1
Brightness:	250 cd/m <sup>2</sup>
Viewable angles:	<ul style="list-style-type: none"><li>• 178 ° - horizontal</li><li>• 178 ° - vertical</li></ul>
Response time:	5 ms
Speakers built-in:	2 x 2 W
Signal connectors:	<ul style="list-style-type: none"><li>• 1x HDMI,</li><li>• 1x VGA,</li><li>• Audio: 1x Jack (for VGA)</li></ul>
Housing type:	Plastic
Monitor mounting standard:	VESA 75
Power supply:	230 V AC
Power consumption:	≤ 25 W (operation)
Monitor control:	OSD - by monitor control keys

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Operation temp:	0 °C ... 40 °C
Weight:	2.64 kg
Dimensions:	<ul style="list-style-type: none"><li>• 500 x 373 x 190 mm (with stand)</li><li>• 500 x 295 x 44 mm (without stand)</li></ul>
Supported languages:	English, French, Spanish, German, Italian
Manufacturer / Brand:	VILUX
Guarantee:	2 years

## PRESENTATION

Front view:



Rear view:



Control keys:



Monitor connectors:



In the kit:



## OUR OPINIONS



- Our tests show that the contrast and viewing angles are slightly smaller than those stated by the manufacturer.