

Code: VM-3402Q

MONITOR DP, HDMI, USB, AUDIO **VM-3402Q** 34 " VILUX

Net: **284.00 EUR** Gross: **284.00 EUR**

An ultra-wide monitor ideal for applications that require a fast-response-time screen. The monitor is compatible with a 21:9 aspect ratio.

The VM-3402Q monitor can work in multi-screen mode, allowing you to display images from two sources simultaneously, e.g. DP + HDMI.



SPECIFICATION

Screen size:	34 "
Native resolution:	3440 x 1440 px
Aspect ratios:	21 : 9
Matrix type:	IPS color matrix, LED backlight, Matte matrix
Contrast:	1000 : 1
Brightness:	300 cd/m ²
Viewable angles:	• 178 ° horizontal • 178 ° vertical
Response time:	1 ms
Speakers built-in:	2 x
Signal connectors:	1 x DisplayPort , 2 x HDMI , 1 x USB , 1 x Audio (Jack 3.5mm socket) 1 x 2.1/5.5 mm socket 12 V DC
Number of displayed colors:	16.7 M
Refresh frequency:	65 Hz
Housing type:	Plastic
Monitor mounting standard:	VESA 100
Robbery protection:	✓
Parameters adjustment:	OSD - by monitor control keys

Main features:	• Multi-screen mode : 2 x 1720 x 1440 px - simultaneous display of images from 2 sources, e.g. DP + HDMI • Fast response time - no image blurring or ghosting • Wide base : Angle adjustment range $\pm 30^\circ$ horizontal, Height adjustment • DP cable included • HDMI cable included
Power supply:	12 V DC / 5 A (power adapter included)
Power consumption:	25 W (operation)
Operation temp:	-10 °C ... 60 °C
Weight:	• 6.4 kg (without stand) • 7.7 kg (with stand)
Dimensions:	• 820 x 365 x 60 mm (without stand) • 820 x 565 ... 435 x 235 mm (with stand)
Manufacturer / Brand:	VILUX
Guarantee:	2 years

PRESENTATION

Front view:



OSD menu control keys:



Side view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Bracket adjustment:



Rear view:



Bottom view:



Connectors:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------