

Code: UT-33D

DIGITAL MULTIMETER UT-33D

Net: 46.85 PLN Gross: 57.63 PLN



UT-33D is a universal digital meter used to measure: voltage, current, resistance.

The meter is equipped with a simple rectangular signal source with a frequency of approx. 50 Hz and an output resistance 47 k Ω .

SPECIFICATION

DC voltage measurement:	200 mV \pm (0.5% + 2) @ 0.1 mV , 2000 mV \pm (0.5% + 2) @ 1 mV , 20 V \pm (0.5% + 2) @ 10 mV , 200 V \pm (0.5% + 2) @ 100 mV , 500 V \pm (0.8% + 2) @ 1 V
AC voltage measurement:	200 V \pm (1.2% + 10) @ 100 mV , 500 V \pm (1.2% + 10) @ 1 V
DC current measurement:	2000 μ A \pm (1.0% + 2) @ 1 μ A , 20 mA \pm (1.0% + 2) @ 10 μ A , 200 mA \pm (1.2% + 2) @ 100 μ A , 10 A \pm (2.0% + 5) @ 10 mA
AC current measurement:	—
Resistance measurement:	200 Ω \pm (0.8% + 5) @ 0.1 Ω , 2 k Ω \pm (0.8% + 2) @ 1 Ω , 20 k Ω \pm (0.8% + 2) @ 10 Ω , 200 k Ω \pm (0.8% + 2) @ 100 Ω , 2 M Ω \pm (0.8% + 2) @ 1 k Ω , 20 M Ω \pm (1.0% + 5) @ 10 k Ω , 200 M Ω \pm (5% + 10) @ 100 k Ω
Capacitance measurement:	—
Inductance measurement:	—
Frequency measurement:	—
Temperature measurement:	—
hFE:	—
Diode test:	✓
Sound signal of the continuity test:	✓

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Checking TTL logic states:	—
RS-232:	—
Main features:	<ul style="list-style-type: none"> • Large, readable LCD display with backlight • Aesthetic and solid construction
Power supply:	9V, type 6F22 battery - included
Dimensions:	133 x 77 x 37 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

PRESENTATION



In the kit:

