

Code: UT-15C

## DIGITAL MULTIMETER UT-15C

Net: 24.76 USD Gross: 30.45 USD



The UT-15C meter allows to measure AC, DC voltages in the range 12 ... 690V. The measurement is carried out automatically when the probes come into contact with the measuring points. The device automatically selects the appropriate measuring range and informs the user about it using LEDs located above the display.

In addition to measuring the voltage, the device allows you to check the continuity of the circuit and measure the phase shift between the two phases of power supply.

**Attention!** The maximum duration of the measurement is 30 sec. After this time, wait about 10 minutes before performing the next measurement.

### SPECIFICATION

DC voltage measurement:	12 V - visual measurement , 24 V ... 690 V $\pm$ (3%+5) @ 1 V
AC voltage measurement:	12 V - visual measurement , 24 V ... 690 V $\pm$ (3%+5) @ 1 V
DC current measurement:	—
AC current measurement:	—
Resistance measurement:	0 ... 400 k $\Omega$
Capacitance measurement:	—
Inductance measurement:	—
Frequency measurement:	—
Temperature measurement:	—
hFE:	—
Diode test:	—
Sound signal of the continuity test:	✓
Checking TTL logic states:	—
RS-232:	—
Main features:	<ul style="list-style-type: none"><li>• Sound signaling</li><li>• Flashlight built-in</li><li>• Aesthetic and solid construction</li><li>• Voltage tester function (one probe measurement using the contact placed on it) - Detection of voltage above 100V results in lighting the diode</li></ul>
Power supply:	2 x 1.5V, type AAA/LR03 battery - included
Dimensions:	280 x 75 x 35 mm
Manufacturer / Brand:	UNI-T

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Guarantee:

2 years

## PRESENTATION

Front view:



Front panel (LED indicators):



Rear view:



Place for batteries 2 x 1.5V AAA:



In the kit:

