

Code: VGA+Y+2AU/VGA+AU

MULTIMEDIA CONVERTER **VGA+Y+2AU/VGA+AU**

Net: **12.30 EUR** Gross: **12.30 EUR**

Converter allows to connect the device equipped only with Component Video output, to the receiver with the VGA input.

Attention! To switch between the Y/VGA mode and the VGA/VGA mode you should keep pressed the "Menu" button for 3 seconds.



SPECIFICATION

Input:	1x VGA 1x Audio (Jack 3.5mm socket) 1x Component Video YPbPr (3x Cinch)
Output:	1x VGA (bypass) 1x Audio (loop-through socket Jack 3.5mm) 1x Cinch (R/L)
Supported resolutions:	480i 480p 576i 576p 720p 1080i 1080p @ 50/60 Hz
Power supply:	5 V DC / 1 A (power adapter included)
Power consumption:	max. 5 W
Operation temp:	-25 °C ... 50 °C
Weight:	0.39 kg
Dimensions:	129 x 105 x 35 mm
Guarantee:	2 years

PRESENTATION

Front panel:



Rear panel:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60