

Code: M-207M

# SINGLE-MODE MEDIA CONVERTER TXRX SET **M-207M** ULTIMODE

Net: **43.60 EUR** Gross: **53.63 EUR**

The M-207M converter allows to change the data stream transmission media from standard STP/UTP cable to single-mode fiber cable.

The device is equipped with SC connector ensuring reliable connections. Optical signal is transmitted and received in the II i III transmission window of 1310/1550 nm.



## SPECIFICATION

Optical connector type:	SC
Number of fibers:	1 pcs
Transmission range:	20 km - Single-mode fiber
Supported standards:	IEEE 802.3, IEEE 802.3u
Port LAN:	1 pcs (RJ-45. UTP/STP)
Transmission speed:	10/100 Mbps
Optical wavelength:	1550 / 1310 nm
Main features:	<ul style="list-style-type: none"><li>• MDI/MDI-X auto detection feature - auto detecting the data transmission mode</li><li>• Auto detection of the bit rate</li><li>• Bi-directional transmission via single fiber</li><li>• LED indicators showing operating status</li><li>• Wavelength-Division Multiplexing technology WDM (Tx 1550nm / Rx 1310nm)</li></ul>
Power supply:	5 V DC / 2 A (power adapter included)
Operation temp:	0 °C ... 50 °C
Weight:	0.176 kg
Dimensions:	105 x 70 x 26 mm - Transmitter or receiver dimensions
Manufacturer / Brand:	ULTIMODE
Guarantee:	2 years

## PRESENTATION

Front view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Rear view:



Top view:



In the kit:

