
Code: MCT12E-BK-IO

PROXIMITY READER **MCT12E-BK-IO** ROGER

Net: 76.61 EUR Gross: 76.61 EUR



Outdoor reader of proximity cards and key-fobs designed to work in the RACS 5 access control and building automation system. Unique 125 kHz standard.

SPECIFICATION

Support:	RACS 5 (Roger)
Cards support:	Unique EM 125kHz
Reading distance of prox-keys:	max. 7 cm
Keyboard built-in:	–
Autonomous operation:	–
Doorbell button:	–
Tamper output:	✔
Communication:	• RS-485, • RACS 5 (Roger)
Main features:	• Tamper protection (detection of removing from mounting surface and enclosure opening) • LED indication • Beep signal • Built-in in/out lines • 3 inputs • 1 Relay output • Two transistor outputs : IO1, IO2 - "Open Collector" (OC) type, max. 15 V DC / 1 A
Power supply:	10 ... 15 V DC
Average current consumption:	~ 50 mA
Operation temp:	-25 °C ... 60 °C
Permissible relative humidity:	10 ... 95 % (non-condensing)
"Index of Protection":	IP65

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Weight:	0.16 kg
Dimensions:	152 x 46 x 23 mm
Manufacturer / Brand:	ROGER
Guarantee:	**3 years**

PRESENTATION

Front panel:




Rear view:



Internal view, after remove the cover:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60