

Code: MCT12M-BK-DES-IO

PROXIMITY READER **MCT12M-BK-DES-IO** ROGER

Net: **153.03 EUR** Gross: **153.03 EUR**



Outdoor reader of proximity cards and key-fobs designed to work in the RACS 5 access control and building automation system. 13.56 MHz S50 DESFire/Plus standard.


SPECIFICATION

Support:	RACS 5 (Roger)
Cards support:	13.56 MHz S50
Reading distance of prox-keys:	max. 7 cm
Keyboard built-in:	—
Doorbell button:	—
Tamper output:	✓
Communication:	RS-485
Main features:	• Tamper protection (detection of removing from mounting surface and enclosure opening) • LED indication • Beep signal • Built-in in/out lines • 3 inputs • 1 Relay output : REL1 - NO/NC, 30 V AC/DC / 1.5 A • Two transistor outputs : IO1, IO2 - "Open Collector" (OC) type, max. 15 V DC / 1 A
Power supply:	10 ... 15 V DC
Average current consumption:	~ 50 mA
Operation temp:	-25 °C ... 60 °C
Permissible relative humidity:	10 ... 95 % (non-condensing)
"Index of Protection":	IP65
Weight:	0.15 kg

Dimensions:	152 x 46 x 23 mm
Manufacturer / Brand:	ROGER
Guarantee:	2 years

PRESENTATION

Front panel:



Rear view:



Internal view, after remove the cover:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------