

Code: UT-4

# COMMUNICATION INTERFACE **UT-4** LAN-RS232/422/485

Net: **166.01 EUR** Gross: **204.19 EUR**

The UT-4 interface enables communication with devices equipped with communication serial port via computer network. The interface is equipped with a serial port on one side, which can be configured to the RS232/RS422/RS485 standards, and with computer network socket operating in the 100BaseT Ethernet standard on other side. The UT-4 module is identified in computer network by IP address, which is assigned to the device during configuration.

The interface is built based on the Digi Connect ME network module of the Digi company. All software tools dedicated to this module can be also using to the UT-4 interface.



## SPECIFICATION

Communication interface:	<ul style="list-style-type: none"><li>• RS-232 : RXD, TXD, RTS, CTS, GND</li><li>• RS-422 : TXA, TXB; RXA, RXB</li><li>• RS-485 : A, B</li></ul>
Ethernet interface:	100 Base-T
Power supply:	10 V ... 15 V DC
Current consumption:	max. 150 mA
Operation temp:	0 °C ... 55 °C
Permissible relative humidity:	10 % ... 90 % (non-condensing)
Weight:	0.106 kg
Dimensions:	100 x 68 x 35 mm
Manufacturer / Brand:	ROGER
Guarantee:	2 years

## PRESENTATION

Front panel view:



Device connectors:



In the kit:

