

Code: RUD-1

# COMMUNICATION INTERFACE **RUD-1** RS-485

Net: **59.63 EUR** Gross: **59.63 EUR**

Converter between serial transmission interfaces of standards USB and RS-485. Unit is powered straight from the USB port of the PC - doesn't require any external power source. Unit can be used to bi-directional transmission (half duplex) with 0 ... 115.2 kbit/s rate.



## SPECIFICATION

|                                |  |
|--------------------------------|--|
| Power supply:                  | 5 V DC from USB port   |
| Current consumption:           | 30 mA  |
| Application:                   | <ul style="list-style-type: none"><li>• Communication with RACS access control system</li><li>• Configuration and management of PR series access controllers from PR Master software</li><li>• Configuration and management of PRTxxEM and PRTxxMF series readers from RARC software</li></ul> |
| Permissible relative humidity: | 0 ... 95 % (non-condensing)  |
| Dimensions:                    | 100 x 31 x 21 mm   |
| Weight:                        | 0.03 kg  |
| Manufacturer / Brand:          | ROGER  |
| Guarantee:                     | 2 years  |

## PRESENTATION

Bottom view:



Top view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



In the kit:



## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|

