

Code: ATLO-KRM-102

## CODE LOCK ATLO-KRM-102

Net: 26.57 EUR Gross: 32.68 EUR



Indoor, autonomous code lock with RFID reader.

Autonomous operation of the device allows the user to:

- Open by using a card or PIN code.
- Remember stored cards or PIN codes.
- Signaling left the door open.
- Acoustic and optical signaling.

Administrator capabilities are following:

- Programming by using the keypad.
- Adding a new card by using the keypad.
- Adding a new card and entering a PIN code.
- Changing the PIN code of the user.
- Deleting the PIN code of the user.
- Setting the lock release time.
- Restoring the default settings.

### SPECIFICATION

Cards support:	Unique EM 125kHz
Reading distance of prox-keys:	3 ... 6 cm
Autonomous operation:	✓
Keyboard built-in:	✓
Communication:	Wiegand 26
Doorbell button:	—
Tamper output:	—
Power supply:	12 V DC ± 10%
Maximal current consumption:	25 mA (Standby mode) 60 mA (operation)
Relay contacts load:	1 A / 12 V
Main features:	<ul style="list-style-type: none"><li>• Number of relay outputs : 1,</li><li>• 2000 indexed users,</li><li>• Identification: Card and/or PIN</li><li>• Blue backlight of the keys</li><li>• Support for door contact and exit button</li><li>• Electric strikes and electromagnetic locks support</li><li>• Reversing bolt support</li><li>• Tamper protection (detection of removing from mounting surface and enclosure opening)</li><li>• Alarm output</li><li>• NO/NC output</li><li>• Possible connection of the external ATLO-R series reader (read in/out access control)</li></ul>
Operation temp:	-45 °C ... 60 °C

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Permissible relative humidity:	10 ... 90 % (non-condensing)
"Index of Protection":	IP40
Housing:	Plastic (ABS)
Color:	Black
Weight:	0.09 kg
Dimensions:	82 x 92 x 21 mm
Manufacturer / Brand:	ATLO
Guarantee:	<b>3 years</b>

## PRESENTATION

Front panel view:



Mounting side view:



In the kit:

