Code: SP-OSM32/MINI

OPTICAL LIGHT SOURCE **SP-OSM32/MINI** 1310 / 1550 nm Spacetronik

Net: 91.93 EUR Gross: 91.93 EUR



The SP-OSM32/MINI Laser light source allows to generate a test light beam with wavelength 1310 nm / 1550 nm. Thanks to this, using any optical power meter you can quickly and accurately assess the status of fiber optics and their connections in the tested installation.

The source may beam on continuous (CW) or intermittent mode on frequency 270 Hz / 1 kHz / 2 kHz. The universal connector allows to connect all optical connectors of 2.5 mm standard, eg SC/FC/ST.

WARNING! Avoid directing the laser beam towards the skin and eyes when using this product.

SPECIFICATION

Optical wavelength:	1310 / 1550 nm
Optical output power:	≥ -7 dBm
Connector type:	Sleeve 2.5 mm
Material:	Plastic
Main features:	• Good output power stability • Large, readable LCD display with backlight • Automatic power-off • Battery charge indicator • The universal connector allows to connect all optical connectors of 2.5 mm standard, eg SC/FC/ST • High durability tool, made from high quality materials • The set includes adapters SC / FC / ST • The device works with both single-mode and multi-mode fibers • Small dimensions • The set includes a practical case • Backup time : 40 h
Power supply:	3 x 1.5 V - Battery type LR3 (AAA) (not included)
Weight:	0.13 kg - Without batteries
Dimensions:	132 x 65 x 29 mm
Manufacturer / Brand:	Spacetronik
Guarantee:	2 years

PRESENTATION

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Front view:



Rear view (place for battery):



Top view:

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Connector:



In the kit:



Device is secured by handy case:

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



OUR OPINIONS

- Solid workmanship.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg