

Code: KT-706

RS-485 KEYBOARD CONTROLLER **KT-706**

Net: **109.69 EUR** Gross: **109.69 EUR**

Device enables quick access to the main functions, such as camera zoom and convenient 3D joystick control. Allows to control the most of camera models at direct mode (presets, routes, vectors control, etc.).
The device has very small dimensions.



SPECIFICATION

Protocols:	Pelco-D, Pelco-P, SAMSUNG, YAAN, SAE
Baud rates:	1200, 2400, 4800, 9600, 19200 bps
Cameras numbers (ID):	0 ... 255
Maximal control distance:	1200 m
Communication standard:	RS-485
Manipulator:	3-axis joystick, Speed proportional to the swing (possibility of zoom control by joystick)
Display:	LCD 2x16 characters
Power supply:	12 V DC / 2 A (power adapter included)
Operation temp. / Relative humidity:	-10 °C ... 50 °C / max. 90 %
Weight:	0.75 kg
Dimensions:	220 x 140 x 98 mm
Guarantee:	2 years

PRESENTATION


Top view:



Keyboard connectors:



In the kit:



OUR OPINIONS



- User friendly and intuitive keyboard interface.
- LCD display with backlight.
- Small dimensions of the device.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------