

Code: KT-608

RS-485 KEYBOARD CONTROLLER **KT-608**

Net: **99.87 EUR** Gross: **99.87 EUR**



SPECIFICATION

Protocols:	Pelco-D, Pelco-P
Baud rates:	1200, 2400, 4800, 9600 bps
Cameras numbers (ID):	0 ... 255
Maximal control distance:	1200 m
Number of controlled devices:	max. 32
Communication standard:	RS-485 RJ-45 socket
Manipulator:	3-axis joystick, Speed proportional to the swing (possibility of zoom control by joystick)
Display:	4 x 20 LCD
Main features:	• 128 presets • scanning • possibility to set tours (with speed, zoom, focus adjustment, etc.)
Power supply:	12 / 0.50 A
Operation temp. / Relative humidity:	0 °C ... 50 °C max. 90 %
Weight:	0.62 kg
Dimensions:	220 x 180 x 100 mm
Guarantee:	2 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Keyboard connectors:



The control operations and functions are very intuitive, status information are presented on the LCD screen:



In the kit:



OUR OPINIONS



- User friendly and intuitive keyboard interface.
- LCD text display with time light function.
- Modern and ergonomic design.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------