

Code: PCM-1210

UNIVERSAL METER **PCM-1210** DVB-T/T2 DVB-S/S2 DVB-C

Net: **153.95 EUR** Gross: **153.95 EUR**



The PCM-1210 allows to measure the TV signals at DVB-T/T2, DVB-S/S2, DVB-C installations. Readable menu will help the operation for any installer.

SPECIFICATION

Output and input:	1 pcs F socket, 1 pcs IEC socket, 1 pcs mini USB
Frequency range:	• 950 MHz ... 2150 MHz - DVB-S / DVB-S2 • 44 MHz ... 870 MHz - DVB-T / DVB-T2 / DVB-C
Signal level:	• 35 ... 90 dBμV - DVB-S / DVB-S2, • 30 ... 100 dBμV - DVB-T / DVB-T2 / DVB-C
LNB power supply:	13 / 18 V, max. 500 mA
Antenna powering:	5 / 12 V
Switching between bandwidths:	0 / 22 kHz
DiSEqC:	DiSEqC 1.0, 1.1, 1.2, USALS systems support
Modulation:	QPSK - DVB-S QPSK / 8PSK - DVB-S2 QPSK / 16-QAM / 64-QAM / 256-QAM - DVB-T 16, 32, 64, 128, 256 QAM - DVB-C
Video signal test:	—
Programming and firmware upgrade:	via USB port
Battery power supply:	• Li-Ion battery 7.4 V / 1400 mAh • 12 V / 1000 mA (power adapter included)

Main features:	• Satellite scanning function • DisEqC automatic identification • Calculation of azimuth and elevation angle • Analysis of the spectrum for the whole frequency band • Easy identification for Quattro LNB • LCD display 2.4 ", 320 x 240 px • Constellation diagram @ DVB-S / DVB-S2 - 8PSK, QPSK, 16APSK, 32APSK • Measurement of C/N, S/N, BER • Measurement of CBER, VBER, SNR, Power measurement - DVB-T / DVB-T2 • High measurement accuracy • The set includes a practical case • Estimated battery operation time ~ 3 h
Weight:	0.238 kg
Dimensions:	177 x 80 x 34 mm
Supported languages:	English, Polish
Manufacturer / Brand:	Digitsat
Guarantee:	2 years

PRESENTATION

Top view:



Bottom view:



In the kit:





PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------