

Code: WS-6933

## SATELLITE METER WS-6933

Net: 60.95 EUR Gross: 60.95 EUR

The WS-6933 satellite meter allows to quick set the satellite dish signal. The WS-6933 is equipped with readable menu, which helps to operate for each installer. The device has implemented over a dozen satellite positions (satellites + transponders).

The WS-6933 model allows to DVB-S2 signals measurement.

**Attention!** The built-in compass is too inaccurate to correctly determine the direction.



### SPECIFICATION

|                                   |                                                                                                                                                                                                                      |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Output and input:                 | — / F socket                                                                                                                                                                                                         |
| Frequency range:                  | 950 MHz ... 2150 MHz                                                                                                                                                                                                 |
| Signal level:                     | -65 ... -25 dBm                                                                                                                                                                                                      |
| LNB power supply:                 | 13/18 V, max. 300 mA                                                                                                                                                                                                 |
| Switching between bandwidths:     | 22 kHz                                                                                                                                                                                                               |
| DiSEqC:                           | 1.0, 1.1                                                                                                                                                                                                             |
| Modulation:                       | QPSK, 8PSK, 16APSK                                                                                                                                                                                                   |
| Symbol rate:                      | 2 ... 45 Msps                                                                                                                                                                                                        |
| SCPC and MCPC support:            | ✓                                                                                                                                                                                                                    |
| Programming and firmware upgrade: | via USB port                                                                                                                                                                                                         |
| Battery power supply:             | Li-Ion battery 800 mAh<br>Power adapter 12 V / 1 A (power adapter included)                                                                                                                                          |
| Display:                          | 240 x 320 " TFT LCD                                                                                                                                                                                                  |
| Main features:                    | <ul style="list-style-type: none"><li>• Sound signaling</li><li>• DiSEqC and 22kHz control support</li><li>• DVB-S signals measurement / DVB-S2 - SD and HD quality channels</li><li>• Flashlight built-in</li></ul> |
| Weight:                           | 0.33 kg                                                                                                                                                                                                              |
| Dimensions:                       | 172 x 85 x 42 mm                                                                                                                                                                                                     |
| Guarantee:                        | 2 years                                                                                                                                                                                                              |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

## PRESENTATION

Device connectors:



In the kit:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|