

Code: AXON-POWER/DIN

## OVERVOLTAGE LIMITER AXON-POWER/DIN

Net: 35.22 EUR Gross: 35.22 EUR



Protection device, protects the devices against lightning discharges or surges in AC 230V power lines. AXON-POWER/DIN is designed to mount on the DIN 35 mm rail.

The condition of correct protection is connecting the AXON-POWER/DIN device to the proper grounding or PE wire.

### SPECIFICATION

Rated voltage:	230 V AC / 50 Hz
Maximal voltage:	250 V AC / 50 Hz
Rated current:	10 A
Protection level Up L/PE, N/PE:	$\leq 1.3$ kV
Protection level Up L/N:	$\leq 3$ kV
Nominal discharge current (L/N, L/PE, N/PE):	4 kA - 8/20 $\mu$ s
Maximum stroke current (L/N, L/PE, N/PE):	10 kA 8/20 $\mu$ s (type 2)
Operation state indication:	✓
Connectors type:	2 x terminals
Housing:	<ul style="list-style-type: none"><li>• Plastic</li><li>• DIN, TS-35 rail mounting</li></ul>
Weight:	0.075 kg
Dimensions:	86 x 58 x 35 mm
Guarantee:	2 years

### PRESENTATION

Device connectors:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Mounting side view:



**PACKAGE**

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

