

Code: CV70-2812/3*P24

VANDALPROOF CAMERA **CV70-2812/3*P24** STANDARD: PAL, 700 TVL

2.8 ... 12 mm

Net: **1 003.32 EUR** Gross: **1 003.32 EUR**

Vandal-proof camera in metal housing with high resolution sensor and wide range of view angle adjustment.

It is equipped with IR illuminator, which is turned on by twilight sensor when illumination conditions are low. Housing construction allows to mount the camera to the ceiling and the wall (image is right oriented in both cases).

Camera module is mounted inside the dome housing, which allows to rotate the camera on any axis. It is equipped with OSD menu controller, which allows to set and change the camera parameters without the need to remove or move the camera.



SPECIFICATION

In package:	24 pcs The price for package
Standard:	PAL
Sensor:	1/3 " Sony EXview HAD II CCD
Digital Image Processor:	DSP Sony Effio-E
Resolution:	700 TVL
Lens:	2.8 ... 12 mm (adjusted by screwdriver, you don't have to open the camera's housing)
View angle:	81 ° ... 23 ° (manufacturer data) 81 ° ... 27 ° (our tests result)
Range of IR illumination:	30 m
S/N ratio:	> 50 dB
Video output:	1 Vpp / 75 Ω
Power supply:	12 V / 430 mA
Main features:	• DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • WDR - Wide Dynamic Range • Motion Detection - max. 4 zones • Privacy zones - max. 8 • Day/Night mode - configurable • Auto White Balance • Mirror - Mirror image • Sharpness - sharper image outlines
OSD menu:	✓
Vandal-proof:	✓
Permissible relative humidity:	max. 95 %
"Index of Protection":	IP66
Housing:	Dome - Metal
Color:	Light graphite

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Operation temp:	-10 °C ... 50 °C
Weight:	0.660 kg
Dimensions:	Ø 120 x 95 mm
Supported languages:	English, Chinese, French, Spanish, Japanese, German, Polish, Portuguese, Russian
Guarantee:	2 years

PRESENTATION

Camera is out from the clamping ring (the OSD menu controller is visible on the cable):



Mounting side view:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



OUR OPINIONS



- OSD controller placed on the cable much simplified the camera configuration.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------