

Code: CV73V-2812/3

PAL VANDALPROOF CAMERA **CV73V-2812/3** 720 TVL, 960H 2.8 ... 12 mm

Net: **51.54 EUR** Gross: **51.54 EUR**

Camera equipped with perfect very high resolution Sony sensor and Sony Effio Digital Image Processor. Due to above, this camera is perfect solution for surveillance systems requiring persons or vehicles recognition, for example at places like: buildings entrance, lobbies, lounges, etc.

It is equipped with IR illuminator, which is turned on by twilight sensor when illumination conditions are low. Housing construction allows to mount the camera to the ceiling and the wall (image is right oriented in both cases).

Camera module is mounted inside the dome housing, which allows to rotate the camera on any axis. It is equipped with OSD menu controller, which allows to set and change the camera parameters without the need to remove or move the camera.



SPECIFICATION

Standard:	PAL
Sensor:	1/3 " Sony EXview HAD II CCD
Digital Image Processor:	DSP Sony Effio-V
Resolution:	720 TVL, 960H
Lens:	2.8 ... 12 mm (adjusted by screwdriver, you don't have to open the camera's housing)
View angle:	81 ° ... 23 ° (manufacturer data) 82 ° ... 28 ° (our tests result)
Range of IR illumination:	30 m
S/N ratio:	> 52 dB
Video output:	1 Vpp / 75 Ω
Power supply:	12 V / 420 mA
Main features:	• Sense-UP - (Slow Shutter) - Increase the sensor sensitivity • DIS - Digital Image Stabilization • ATR - Wide Dynamic Range • DNR - Digital Noise Reduction • IR illuminator optimization • EZOOM - Digital Zoom off • HLC - High Light Compensation (spot) • BLC - configurable Back Light Compensation • Privacy zones - max. 15 • Motion Detection • Sharpness - sharper image outlines • Monitor type correction - LCD/CRT • Day/Night mode - configurable
OSD menu:	✓
Vandal-proof:	✓
Permissible relative humidity:	max. 95 %
"Index of Protection":	IP66
Housing:	Dome - Metal

Color:	Dark graphite
Operation temp:	-10 °C ... 50 °C
Weight:	0.61 kg
Dimensions:	Ø 120 x 95 mm
Guarantee:	2 years

PRESENTATION

Camera is out from the clamping ring (the OSD menu controller is visible on the cable):




Mounting side view:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



OUR OPINIONS



- OSD controller placed on the cable much simplified the camera configuration.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------