MONITOR VGA, 2XVIDEO, HDMI, AUDIO, REMOTE CONTROLLER **VMT-176M** 17 " VILUX

Net: 405.57 EUR Gross: 405.57 EUR

Professional CCTV monitor - solid metal housing and additional layer for matrix protection. The LED matrix illumination technology allows to real colors reproduction, 40% lower current consumption and much lower failure rate compared to normal LCD monitors with CCFL illumination.

The control keys are placed outside of monitor working area. This solution allows to place the monitor inside housing to protect it against change any settings by other people.

This model is equipped with all kinds of inputs, what allows to display an image from any kind of signals using in CCTV systems.

A front of monitor housing and screen are perfectly matched. That allows to use an extra vandal-proof glass without any risk of negative light reflections between glass and the screen. Monitor is designed to the display of advertising spots from computer in public places such as waiting rooms, etc. Very interesting solution is placing the speakers of the back side of housing. It does not bother listening to the AUDIO from the recorder at the same time does not reduce the area of the monitor front panel.

The device is designed to continuous work in closed spaces.

Attention! No batteries inside remote controller (1x BAT-CR2032).



SPECIFICATION

Screen size:	17 "
Native resolution:	1280 x 1024 px
Aspect ratios:	5:4
Matrix type:	TFT-LCD color matrix , LED backlight, Glossy matrix
Supported standards:	PAL/NTSC
Contrast:	1000 :1
Brightness:	250 cd/m ²
Viewable angles:	170 ° horizontal 170 ° vertical
Response time:	5 ms
Speakers built-in:	2 x 2.5 W
Signal connectors:	Composite Video (BNC) sockets: 2x in, 1x out 1x VGA 1x HDMI Audio: 1x Jack (for VGA) 2x Cinch L/R (for Video 1/2)
Housing type:	Metal
Monitor mounting standard:	VESA 100
Power supply:	12 V DC / 3 A (power adapter included)

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

2024-05-10

Power consumption:	• max. 20 W (operation) • < 1 W (Standby mode)
Monitor control:	OSD - by IR remote controller or monitor control keys - No batteries inside remote controller
Main features:	3D Comb Filter 3D Noise Reduction Auto Picture Adjustment
Operation temp:	-20 °C 60 °C
Weight:	4.3 kg
Dimensions:	368 x 315 x 65 mm
Supported languages:	English, Chinese, French, Spanish, German, Polish, Portuguese, Russian, Italian
Manufacturer / Brand:	VILUX
Guarantee:	2 years

PRESENTATION



Side view (control keys visible):

2024-05-10 2/4



Monitor connectors:



In the kit:



OUR OPINIONS



 \circ LED matrix illumination technology. The VILUX company - relatively young, but very dynamic company entering to European market has specialized own production at CCTV monitors and their results in our opinion are really good.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm Gross Weight: 0 kg