

Code: F/RG6/PRO

COMPRESSION PLUG F/RG6/PRO

Net: 0.27 EUR Gross: 0.33 EUR

The F/RG6/PRO compression plug, apart from high-quality feature, is also characterized by an integrated seal securing the connector against water penetration.



SPECIFICATION

Connector type:	"F" Plug
Attachment of connector elements:	Compression mounting
Application:	Coaxial cable
Dielectric diameter:	max. 4.8 mm
Wire mounting:	—
Cable diameter:	max. 8.0 mm
Shield fastening:	Compression mounting
Watertightness:	✓
Example of application:	<ul style="list-style-type: none">• RG6• Triset113
Main features:	<ul style="list-style-type: none">• Watertight connection with cable and "F" connector• Properly compressed connection is highly resistant to break• Very easy and quick assembly• Corrosion resistance• Very low loss in the whole operating band• To crimp use the crimping tool HTL-548 / HT-5082R
Weight:	0.009 kg
Dimensions:	Ø 14.5 mm x 42 mm
Guarantee:	2 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

