

Code: RE-2K

## RADIO CONTROLLER **RE-2K** SATEL

Net: **30.81 USD** Gross: **37.90 USD**

The RE-2K radio remote controller enables remote control of the electrical equipment by means of radio transmitters (remote keyfobs). The RE-1K is one-channel controller, the RE-2K is two-channel controller. Both types of controllers can work with maximal 16 remote keyfobs.




### SPECIFICATION

Operating range in open area:	to 100 m
Number of controlled outputs:	2
Adjustment range of changeover time in monostable mode:	1 s ... 250 s
Maximum current switched over by relay at DC 24V:	2 A
Current-carrying capacity of SS (OC) output:	500 mA
Frequency range:	433.05 MHz ... 434.79 MHz
The KEELOQ code-hopping technology:	✓
Operation temp:	0 °C ... 55 °C
Receiver operation temperature:	-20 °C ... 55 °C
Dimensions:	72 x 118 x 24 mm
Type of remote keyfob battery:	23 A 12 V
Power supply:	DC 12 V
Current consumption (min. / max.):	16 mA / 60 mA
Manufacturer / Brand:	SATEL
Guarantee:	2 years

### PRESENTATION

View after remove the cover:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

In the kit:

