

Code: BCS-V-NVR0401A-4KE-4P

## NVR **BCS-V-NVR0401A-4KE-4P** 4 CHANNELS, 4 PoE BCS View

Net: **260.93 EUR** Gross: **260.93 EUR**

The BCS-V-NVR0401A-4KE-4P digital recorder is a professional device using in IP surveillance systems.



### SPECIFICATION

|                                     |                                                                                                                                 |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Standard:                           | TCP/IP                                                                                                                          |
| Supported resolutions:              | max. 8.3 Mpx - 3840 x 2160 px, 4K UHD                                                                                           |
| Video outputs:                      | 1 pcs HDMI 4K<br>1 pcs VGA                                                                                                      |
| Audio support:                      | 4 Channels - Audio from cameras                                                                                                 |
| Audio inputs:                       | 1 pcs CINCH                                                                                                                     |
| Audio outputs:                      | 1 pcs CINCH                                                                                                                     |
| Image compression method:           | H.265+ / H.265 / H.264+ / H.264                                                                                                 |
| Bitrate:                            | max. 40 Mbps                                                                                                                    |
| Supported hard drives:              | 1 x 8 TB SATA                                                                                                                   |
| Recording modes:                    | Manual, Sensor, Motion detection, Schedule                                                                                      |
| External storage devices backup:    | Backup to USB drive (pendrive, external drive)                                                                                  |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow<br>1/4 channel synchronous playback |
| Network functions:                  | Live image view, Playback the records, Backup the records<br>Web Server built-in, CMS application<br>max. 16 on-line users      |
| Network protocols:                  | TCP/IP, DHCP, IPv4/IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS                            |
| ONVIF:                              | ✓                                                                                                                               |
| Default admin user / password:      | admin / -<br>The administrator password should be set at the first start                                                        |
| Default IP address:                 | 192.168.1.64                                                                                                                    |
| Web browser access ports:           | 80                                                                                                                              |
| PC client access ports:             | Port no.: 8000 or access by a cloud (P2P)                                                                                       |
| Mobile client access ports:         | 8000                                                                                                                            |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|                                  |                                                                                                                                                                                 |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mobile phones support:           | Port no.: 8000 or access by a cloud (P2P)<br>• Android: Free application <a href="#">BCS Manager</a><br>• iOS (iPhone): Free application <a href="#">BCS Manager</a>            |
| RTSP URL:                        | • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream<br>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream |
| USB:                             | 2 pcs USB 2.0                                                                                                                                                                   |
| Alarm inputs / outputs:          | 4 / 1                                                                                                                                                                           |
| PTZ control:                     | IP Speed Dome Cameras                                                                                                                                                           |
| Motion Detection:                | ✓                                                                                                                                                                               |
| Intelligent Image Analysis:      | —                                                                                                                                                                               |
| Mouse support:                   | ✓                                                                                                                                                                               |
| IR remote controller in the set: | —                                                                                                                                                                               |
| Switch PoE:                      | 4-port PoE Switch built-in 802.3af/at, 25.5 W / Channel                                                                                                                         |
| Maximum total switch load:       | 50 W                                                                                                                                                                            |
| Power supply:                    | 48 V DC / 1.35 A (power adapter included)                                                                                                                                       |
| Operation temp:                  | -10 °C ... 55 °C                                                                                                                                                                |
| Weight:                          | 1.15 kg                                                                                                                                                                         |
| Dimensions:                      | 315 x 240 x 48 mm                                                                                                                                                               |
| Supported languages:             | Polish, English                                                                                                                                                                 |
| Manufacturer / Brand:            | BCS View                                                                                                                                                                        |
| Guarantee:                       | <b>3 years</b>                                                                                                                                                                  |

## PRESENTATION

Front panel:



Rear panel:



In the kit:



**PACKAGE**

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|

