

Code: BCS-L-SNVR0401

## NVR **BCS-L-SNVR0401** 4 CHANNELS BCS Line

Net: **140.17 EUR** Gross: **140.17 EUR**



### SPECIFICATION

|                                     |                                                                                                                                                                                    |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                           | TCP/IP                                                                                                                                                                             |
| Supported resolutions:              | max. 12 Mpx - 4000 x 3000 px                                                                                                                                                       |
| Video outputs:                      | 1 pcs HDMI<br>1 pcs VGA                                                                                                                                                            |
| Audio support:                      | 4 Channels - Audio from cameras                                                                                                                                                    |
| Audio inputs:                       | 1 pcs CINCH                                                                                                                                                                        |
| Audio outputs:                      | 1 pcs CINCH                                                                                                                                                                        |
| Image compression method:           | H.265+ / H.265 / H.264+ / H.264                                                                                                                                                    |
| Bitrate:                            | max. 80 Mbps                                                                                                                                                                       |
| Supported hard drives:              | 1 x 16 TB SATA                                                                                                                                                                     |
| Recording modes:                    | Manual, Motion Detection, Schedule                                                                                                                                                 |
| External storage devices backup:    | Backup to USB drive (pendrive, external drive)                                                                                                                                     |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow<br>Advanced searching (to the one second accuracy)<br>1/4 channel synchronous playback |
| Network interface:                  | 1 x RJ-45 10/100 Base-TX                                                                                                                                                           |
| Network functions:                  | Full support via network, Remote records copying, Web Server built-in                                                                                                              |
| Network protocols:                  | HTTP, HTTPS, TCP/IP, IPv4, RTSP, UDP, NTP, DHCP, DNS, SMTP, UPnP, IP Filter, DDNS, Alarm Server, IP Search, P2P                                                                    |
| ONVIF:                              | ✓                                                                                                                                                                                  |
| Default IP address:                 | 192.168.1.108                                                                                                                                                                      |
| Default admin user / password:      | admin / admin                                                                                                                                                                      |

|                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mobile phones support:           | Port no.: 37777 or access by a cloud (P2P)<br>• Android: Free application <a href="#">BCS Manager</a><br>• iOS (iPhone): Free application <a href="#">BCS Manager</a>                                                                                                                                                                                                                                                                   |
| Web browser access ports:        | 80, 37777                                                                                                                                                                                                                                                                                                                                                                                                                               |
| PC client access ports:          | 37777                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Mobile client access ports:      | 37777                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| RTSP URL:                        | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream<br>rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream                                                                                                                                                                                                                                                         |
| USB:                             | 2 pcs USB 2.0                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Serial ports:                    | —                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Alarm inputs / outputs:          | —                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| PTZ control:                     | IP Speed Dome Cameras                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Motion Detection:                | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Intelligent Image Analysis:      | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Main features:                   | <ul style="list-style-type: none"> <li>• CMS application</li> </ul> <p>Functions implemented in cooperation between the recorder and cameras that support these functions</p> <ul style="list-style-type: none"> <li>• Advanced peripheral protection functions: intrusion, crossing line with separate rules for vehicles and pedestrians</li> <li>• SMD PLUS - searching for an object classified as: human, motor vehicle</li> </ul> |
| Mouse support:                   | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| IR remote controller in the set: | —                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Switch PoE:                      | —                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Power supply:                    | 12 V DC / 1.5 A (power adapter included)                                                                                                                                                                                                                                                                                                                                                                                                |
| Power consumption:               | max. 10 W (without HDD)                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Operation temp:                  | -10 °C ... 55 °C                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Weight:                          | 0.45 kg                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Dimensions:                      | 206 x 205 x 48 mm                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Supported languages:             | English, Polish                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Manufacturer / Brand:            | BCS Line                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Guarantee:                       | <b>3 years</b>                                                                                                                                                                                                                                                                                                                                                                                                                          |

## PRESENTATION

Rear panel:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



In the kit:



#### PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|