Code: DHI-NVR4108-P-4KS2

# NVR **DHI-NVR4108-P-4KS2** 8 CHANNELS + 4-PORT POE SWITCH DAHUA

Net: 230.09 EUR Gross: 230.09 EUR



**SPECIFICATION**

| | |
|---|---|
| Standard: | TCP/IP |
| Supported resolutions: | 8 @ 3840 x 2160 px,<br>8 @ 3072 x 2048 px,<br>8 @ 2560 x 1920 px,<br>8 @ 2048 x 1536 px,<br>8 @ 1920 x 1080 px,<br>8 @ 1280 x 720 px,<br>8 @ 704 x 576 px |
| Video outputs: | 1 pcs HDMI<br>1 pcs VGA |
| Audio support: | 8 Channels - Audio from cameras |
| Audio inputs: | 1 pcs CINCH - External microphone input |
| Audio outputs: | 1 pcs CINCH |
| Image compression method: | H.265 / H.264 / MJPEG |
| Maximal total frame rate: | 200 fps @ 3840 x 2160 px,<br>200 fps @ 3072 x 2048 px,<br>200 fps @ 2560 x 1920 px,<br>200 fps @ 2048 x 1536 px,<br>200 fps @ 1920 x 1080 px,<br>200 fps @ 1280 x 720 px,<br>200 fps @ 704 x 576 px |
| Supported hard drives: | 1 x 6 TB SATA |
| Recording modes: | Manual, Motion Detection, Schedule |
| Network protocols: | HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, IP Filter, PPPoE, FTP, IP Search, ONVIF 2.4 |
| External storage devices backup: | Backup to USB drive (pendrive, external drive) |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow<br>Advanced searching (to the one second accuracy)<br>All channels synchronous playback, Smart Search function |
| Bitrate: | max. 80 Mbps |

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

| | |
|---|---|
| Network functions: | Full support via network, Remote records copying, Web Server built-in<br>max. 128 on-line users |
| ONVIF: | 2.4 |
| Mobile phones support: | Port no.: 37777 or access by a cloud (P2P)<br>• Android: Free application DMSS, Android: Free application IMOU<br>• iOS (iPhone): Free application DMSS, iOS (iPhone): Free application IMOU<br><br>See how to configure the P2P function in Dahua recorders and how to enable the mobile application |
| Default admin user / password: | admin / admin |
| Default IP address: | 192.168.1.108 |
| Web browser access ports: | 80, 37777 |
| PC client access ports: | 37777 |
| Switch PoE: | 4-port PoE Switch built-in, 25.5 W / Channel, PoE (802.3af/at) |
| Mobile client access ports: | 37777 |
| Maximum total switch load: | 50 W (at full load) |
| RTSP URL: | rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream<br>rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream |
| Alarm inputs / outputs: | – |
| PTZ control: | IP Speed Dome Cameras |
| Motion Detection: | 22 x 18 motion zones - after motion detection records detected channels only |
| Intelligent Image Analysis: | ✔ |
| Mouse support: | ✔ |
| IR remote controller in the set: | – |
| Power supply: | 48 V DC / 1.5 A (power adapter included) |
| Weight: | 0.50 kg |
| Dimensions: | 205 x 205 x 46 mm |
| Supported languages: | English, Polish |
| Country of origin: | China |
| Manufacturer / Brand: | DAHUA |
| Guarantee: | **3 years** |

**PRESENTATION**

Top view:




Rear panel:



In the kit:



Example captures of device interface:







**OUR OPINIONS**

- Audio transmission via network.

**PACKAGE**

| | |
|---|---|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60