

Code: BCS-V-NVR0802-4KE

NVR **BCS-V-NVR0802-4KE** 8 CHANNELS BCS View

Net: **265.52 EUR** Gross: **265.52 EUR**

The BCS-V-NVR0802-4KE digital recorder is a professional device using in IP surveillance systems. The H.265 / H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity.



SPECIFICATION

Standard:	TCP/IP
Supported resolutions:	max. 8 Mpx - 3840 x 2160 px, 4K UHD
Video outputs:	1 pcs HDMI 4K 1 pcs VGA There is a possibility to configure a SPOT function on one of the output
Audio support:	8 Channels - Audio from cameras
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MPEG-4
Supported hard drives:	2 x 6 TB SATA
Recording modes:	Manual, Motion Detection, Schedule
Network protocols:	TCP/IP, DHCP, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP, HTTPS, P2P, ONVIF
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	DHCP or 192.168.1.64
Web browser access ports:	80
PC client access ports:	Port no.: 8000 or access by a cloud (P2P)
Mobile client access ports:	8000
RTSP URL:	• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow
Bitrate:	max. 80 Mbps
Network functions:	Live image view, Playback the records, Backup the records

ONVIF:	✓
Intelligent Image Analysis:	crossing the line (tripwire), intrusion
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) • Android: Free application BCS View • iOS (iPhone): Free application BCS View
Alarm inputs / outputs:	4 / 1
PTZ control:	IP Speed Dome Cameras
USB:	1 pcs USB 2.0 1 pcs USB 3.0
Motion Detection:	✓
Mouse support:	✓
IR remote controller in the set:	—
Operation temp:	-10 °C ... 55 °C
Power supply:	12 V DC / 3.33 A (power adapter included)
Weight:	1.77 kg
Dimensions:	385 x 315 x 52 mm
Supported languages:	Polish, English
Manufacturer / Brand:	BCS View
Guarantee:	3 years

PRESENTATION

Front panel:



Rear panel:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------