

Code: APTI-N0901-4P-I2

NVR APTI-N0901-4P-I2 9 CHANNELS, 4 PoE

Net: 95.38 EUR Gross: 95.38 EUR

The APTI-N0901-4P-I2 digital recorder is a professional device applicable in surveillance systems. The H.265 / H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.

Attention! The built-in PoE switch only supports APTI cameras.



SPECIFICATION

Standard:	TCP/IP
Supported resolutions:	max. 8 Mpx - 3840 x 2160 px, 4K UHD
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio support:	9 Channels - Audio from cameras
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.265, H.264
Supported hard drives:	1 x 8 TB SATA
Recording modes:	Manual, Motion Detection, Schedule
Network protocols:	TCP/IP, HTTP, HTTPS, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, P2P, PPPoE
External storage devices backup:	Records backup at (.avi) format to USB (pendrive)
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, fast Playback max. 4 cameras in the same time @ 1080p
Bitrate:	80 Mbps
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters
ONVIF:	✓
Mobile phones support:	Port no.: 6000 or access by a cloud (P2P) • Android: Free application BitVision , Android: Free application iVMS320 • Android: Free application BitVision , iOS: Free application iVMS320
Default admin user / password:	admin / 12345
Default IP address:	192.168.1.88
Web browser access ports:	80, 5000, 554
PC client access ports:	80, 5000, 554
Mobile client access ports:	80, 5000, 554
Alarm inputs / outputs:	4 / 1
PTZ control:	IP Speed Dome Cameras

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Motion Detection:	Split the screen into zones : 24 x 18 motion zones
Main features:	Support for intelligent image analysis, available in cameras from the APTI-AI series
USB:	2 pcs USB 2.0
Mouse support:	✓
IR remote controller in the set:	—
Switch PoE:	4-port PoE Switch built-in : 30 W / Channel - 802.3af/at, max. 50 W (total)
Operation temp:	-10 °C ... 55 °C
Power supply:	52 V DC / 1.25 A
Weight:	0.75 kg
Dimensions:	260 x 235 x 45 mm
Supported languages:	Polish, English, Bulgarian, Czech, French, Greek, Spanish, German, Portuguese, Russian, Turkish, Hungarian, Italian
Manufacturer / Brand:	APTI
Guarantee:	2 years

PRESENTATION

Front panel:



Rear panel:



In the kit:



See how to mount a hard disk drive and configure the recorder:

:

PACKAGE



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

