

Code: DS-7608NXI-I2/8P/S(E)

## NVR **DS-7608NXI-I2/8P/S(E)** 8 CHANNELS, 8 PoE ACUSENSE Hikvision

Net: **784.45 EUR** Gross: **784.45 EUR**

NVR equipped with advanced functions of intelligent image analysis.



### SPECIFICATION

|                                     |                                                                                                                                                                                                                                                                              |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                           | TCP/IP                                                                                                                                                                                                                                                                       |
| Supported resolutions:              | max. 32 Mpx                                                                                                                                                                                                                                                                  |
| Video outputs:                      | 1 pcs HDMI 4K<br>1 pcs VGA<br>1 pcs CVBS<br>There is a possibility to configure a SPOT function on one of the output                                                                                                                                                         |
| Audio support:                      | <ul style="list-style-type: none"><li>• 8 Channels - Audio from cameras</li><li>• Bi-directional audio streaming support</li></ul>                                                                                                                                           |
| Audio inputs:                       | 1 pcs CINCH                                                                                                                                                                                                                                                                  |
| Audio outputs:                      | 1 pcs CINCH                                                                                                                                                                                                                                                                  |
| Image compression method:           | H.265+ / H.265 / H.264+ / H.264                                                                                                                                                                                                                                              |
| Bitrate:                            | max. 80 Mbps                                                                                                                                                                                                                                                                 |
| Supported hard drives:              | 2 x 14 TB SATA                                                                                                                                                                                                                                                               |
| Recording modes:                    | Manual, Sensor, Motion detection, Schedule                                                                                                                                                                                                                                   |
| External storage devices backup:    | Backup to USB drive (pendrive, external drive)                                                                                                                                                                                                                               |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow<br>Advanced searching (to the one second accuracy)<br>All channels synchronous playback, Smart Search function<br>Records playback from max. 8 channels in the same time @ 1080p |
| Network interface:                  | 1 x RJ-45 10/100/1000 Base-TX                                                                                                                                                                                                                                                |
| Network functions:                  | <ul style="list-style-type: none"><li>• Live image view, Playback the records, Backup the records</li><li>• max. 128 on-line users - iVMS-4200 application</li></ul>                                                                                                         |
| Network protocols:                  | TCP/IP, DHCP, IPv4/IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS                                                                                                                                                                         |
| ONVIF:                              | ✓                                                                                                                                                                                                                                                                            |
| Default IP address:                 | 192.168.1.64                                                                                                                                                                                                                                                                 |
| Default admin user / password:      | admin / -<br>The administrator password should be set at the first start                                                                                                                                                                                                     |

|                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mobile phones support:           | Port no.: 8000 or access by a cloud (P2P)<br>Android: Free application <a href="#">Hik-Connect</a><br>iOS: Free application <a href="#">Hik-Connect</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Web browser access ports:        | 80, 8000                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| PC client access ports:          | 8000                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Mobile client access ports:      | 8000                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| RTSP URL:                        | <ul style="list-style-type: none"> <li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream</li> <li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| USB:                             | 1 pcs USB 2.0<br>1 pcs USB 3.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Serial ports:                    | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Alarm inputs / outputs:          | 4 / 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| PTZ control:                     | IP Speed Dome Cameras                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Motion Detection:                | 2.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Intelligent Image Analysis:      | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Main features:                   | <ul style="list-style-type: none"> <li>• NVR from the AcuSense series</li> <li>• Intelligent Image Analysis : crossing the line (tripwire), intrusion, Motion detection with human/vehicle silhouette recognition, Face recognition</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Comparison of faces with images from the database</li> <li>• Support for up to 16 face databases, including 50 000 face images</li> <li>• Smart search for a person based on a face photo</li> <li>• Cooperation with POS (Point of Sale) terminals</li> </ul> <p>Functions implemented in cooperation between the recorder and cameras that support these functions</p> <ul style="list-style-type: none"> <li>• ANPR</li> <li>• people counting</li> </ul> |
| Mouse support:                   | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| IR remote controller in the set: | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Switch PoE:                      | 8-port PoE Switch built-in, 25.5 W / Channel - PoE (802.3af/at)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Maximum total switch load:       | 150 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Power supply:                    | 100 ... 240 V AC / 50 ... 60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Power consumption:               | max. 30 W (without HDD)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Operation temp:                  | -10 °C ... 55 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Weight:                          | 2.47 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Dimensions:                      | 380 x 325 x 52 mm, RACK 19", 1U                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Supported languages:             | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Manufacturer / Brand:            | Hikvision                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| SAP Code:                        | 303618728                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Guarantee:                       | <b>3 years</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

## PRESENTATION

Front panel:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



Rear panel:



See how to mount a hard disk drive and configure the recorder:

:

In the kit:



## OUR OPINIONS



- The DS-7608NXI-I2/8P/S(E) is equipped with USB 3.0 port allowing to fast records backup.

## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60