

Code: BCS-L-NVR0802-A-4KE-8P(2)

## NVR **BCS-L-NVR0802-A-4KE-8P(2)** 8 CHANNELS, 8 PoE BCS Line

Net: **554.61 EUR** Gross: **554.61 EUR**



### SPECIFICATION

|                                     |                                                                                                                                                                                                                         |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                           | TCP/IP                                                                                                                                                                                                                  |
| Supported resolutions:              | max. 16 Mpx - 4592 x 3056 px                                                                                                                                                                                            |
| Video outputs:                      | 1 pcs HDMI 4K<br>1 pcs VGA                                                                                                                                                                                              |
| Audio support:                      | 8 Channels - Audio from cameras                                                                                                                                                                                         |
| Audio inputs:                       | 1 pcs CINCH                                                                                                                                                                                                             |
| Audio outputs:                      | 1 pcs CINCH                                                                                                                                                                                                             |
| Image compression method:           | H.265 / H.265+ / H.264 / H.264+ / MJPEG                                                                                                                                                                                 |
| Supported hard drives:              | 2 x 16 TB SATA III                                                                                                                                                                                                      |
| Recording modes:                    | Manual, Sensor, Motion detection, Schedule                                                                                                                                                                              |
| Network protocols:                  | HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search, P2P, Auto Register                                                                         |
| External storage devices backup:    | Backup to USB drive (pendrive, external drive)                                                                                                                                                                          |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow<br>Advanced searching (to the one second accuracy)<br>All channels synchronous playback, Smart Search function              |
| Bitrate:                            | max. 256 Mbps                                                                                                                                                                                                           |
| Network functions:                  | <ul style="list-style-type: none"><li>• Full support via network</li><li>• Remote records copying</li><li>• Web Server built-in max. 128 on-line users</li></ul>                                                        |
| ONVIF:                              | ✓                                                                                                                                                                                                                       |
| Mobile phones support:              | Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">BCS Manager</a></li><li>• iOS (iPhone): Free application <a href="#">BCS Manager</a></li></ul> |
| Default IP address:                 | 192.168.1.108                                                                                                                                                                                                           |
| Default admin user / password:      | admin / -<br>The administrator password should be set at the first start                                                                                                                                                |
| Web browser access ports:           | 80, 37777                                                                                                                                                                                                               |
| PC client access ports:             | 37777                                                                                                                                                                                                                   |
| Mobile client access ports:         | 37777                                                                                                                                                                                                                   |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RTSP URL:                        | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream<br>rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream                                                                                                                                                                                                                                                                                   |
| Alarm inputs / outputs:          | 4 pcs / 2 pcs - Relay output                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| PTZ control:                     | Speed Dome cameras, motor units, Motozoom cameras/lenses support                                                                                                                                                                                                                                                                                                                                                                                                  |
| Intelligent Image Analysis:      | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Motion Detection:                | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| USB:                             | 1 pcs USB 2.0<br>1 pcs USB 3.0                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Main features:                   | Functions implemented in cooperation between the recorder and cameras that support these functions<br><ul style="list-style-type: none"> <li>• Fisheye-Dewarping - correction of the "fish eye" view to the perspective view</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its Cooperation with POS (Point of Sale) terminals</li> </ul> |
| Mouse support:                   | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| IR remote controller in the set: | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Switch PoE:                      | 8-port PoE Switch built-in, 25.5 W / Channel, PoE (802.3af/at)                                                                                                                                                                                                                                                                                                                                                                                                    |
| Maximum total switch load:       | 130 W                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Power supply:                    | 100 ... 240 V AC @ 50 / 60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Operation temp:                  | -10 °C ... 55 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Weight:                          | 2.58 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Dimensions:                      | 374 x 320 x 53 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Supported languages:             | Polish, English                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Manufacturer / Brand:            | BCS Line                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Guarantee:                       | <b>3 years</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

## PRESENTATION

Front panel:



Rear panel:



In the kit:



## OUR OPINIONS



- Bi-directional audio transfer via network.

## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|

