

Code: FLEX-842

NVR **FLEX-842** 8 CHANNELS

Net: **105.93 EUR** Gross: **105.93 EUR**

The FLEX-842 digital recorder is a professional device applicable in surveillance systems. The H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



SPECIFICATION

Standard:	TCP/IP
Supported resolutions:	8 @ 1920 x 1080 px, 8 @ 1280 x 720 px
Audio support:	8 Channels
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio inputs:	Audio from cameras
Audio outputs:	—
Image compression method:	H.264
Maximal total frame rate:	200 fps @ 1920 x 1080 px, 200 fps @ 1280 x 720 px
Supported hard drives:	2 x 4 TB SATA
Operation modes:	Firmware V4.0[20150124] : • 8 x Main stream (1920 x 1080) + 8 x Sub stream (640 x 480) + 1 Channel played simultaneously • 8 x Main stream (1280 x 960) + 8 x Sub stream (640 x 480) + 1 Channel played simultaneously • 8 x Main stream (1280 x 720) + 8 x Sub stream (640 x 360) + 4 Channels played simultaneously Firmware V4.0[20140415] : • 8 x Main stream (1920 x 1080) + 8 x Sub stream (640 x 480) + 1 Channel played simultaneously • 8 x Main stream (1280 x 720) + 8 x Sub stream (640 x 360) + 4 Channels played simultaneously
Recording modes:	Manual, Sensor, Motion detection, Schedule
Network protocols:	ONVIF, I8, I9, RTSP
External storage devices backup:	Records backup at .mp4 / .avi format to USB (pendrive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow
Network functions:	Live image view, Playback the records, Backup the records
Bitrate:	40 Mbps
ONVIF:	✓

Mobile phones support:	Port 5053 • Android: Free application MEye • iOS (iPhone): Free application Meye • Windows Phone: Free application Meye Access by a cloud (P2P) • Android: Free application Goolink • iOS (iPhone): Free application Goolink
Alarm inputs / outputs:	2 / 1
Operation temp:	-10 °C ... 55 °C
PTZ control:	RS-485 - PELCO-D/P + Many protocols
Motion Detection:	22 x 18 motion zones
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 4 A
Weight:	1.63 kg
Dimensions:	360 x 244 x 54 mm
Supported languages:	English, Polish
Country of origin:	China
Guarantee:	2 years

PRESENTATION

Front panel:



Rear panel:




In the kit:



OUR TESTS

See the configuration of the APTI series cameras operation modes with the recorders:



OUR OPINIONS



- DVR records smooth image at good quality with audio for each camera.



- To provide the connection from Internet (WAN) to a DVR connected to the LAN, you should forward on router the following ports: 80, 554, 5050, 5051, 5052, 5053.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60