

Code: DS-7616NI-I2/16P

## IP DVR **DS-7616NI-I2/16P** 16 CHANNELS +16-PORT SWITCH POE Hikvision

Net: **3 058.00 PLN** Gross: **3 761.34 PLN**



### SPECIFICATION

Standard:	TCP/IP
Supported resolutions:	16 @ 4000 x 3000 px, 16 @ 3840 x 2160 px, 16 @ 3072 x 2048 px, 16 @ 2592 x 1944 px, 16 @ 2560 x 1944 px, 16 @ 2560 x 1440 px, 16 @ 2048 x 1536 px, 16 @ 1920 x 1536 px, 16 @ 1920 x 1080 px, 16 @ 1280 x 720 px, 16 @ 704 x 576 px
Video outputs:	1 pcs HDMI 1 pcs VGA Possibility to configure one of the video output as a SPOT output
Audio support:	<ul style="list-style-type: none"><li>• 16 Channels - Audio from cameras</li><li>• Bi-directional audio streaming support</li></ul>
Audio inputs:	1 pcs Microphone, CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.265 / H.264 / H.264+ / MPEG-4
Maximal total frame rate:	400 fps @ 4000 x 3000 px, 400 fps @ 3840 x 2160 px, 400 fps @ 3072 x 2048 px, 400 fps @ 2592 x 1944 px, 400 fps @ 2560 x 1944 px, 400 fps @ 2560 x 1440 px, 400 fps @ 2048 x 1536 px, 400 fps @ 1920 x 1536 px, 400 fps @ 1920 x 1080 px, 400 fps @ 1280 x 720 px, 400 fps @ 704 x 576 px
Supported hard drives:	2 x 6 TB SATA III
Recording modes:	Manual, Sensor, Motion detection, Schedule
Network protocols:	TCP/IP, PPPoE, DHCP, Hik Cloud P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF
External storage devices backup:	Backup to USB drive (pendrive)

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function Records playback from max. 16 channels in the same time @ 1080p or max. 4 @ 4K
Bitrate:	max. 160 Mb/s
Network functions:	<ul style="list-style-type: none"> <li>• Live image view, Playback the records, Backup the records</li> <li>• max. 128 on-line users - iVMS-4200 application</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> </ul>
ONVIF:	✓
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) Android: Free application <a href="#">iVMS-4500</a> or <a href="#">Hik-Connect</a> iOS (iPhone): Free application <a href="#">iVMS-4500</a> or <a href="#">Hik-Connect</a>
Default IP address:	192.168.1.64
Default admin user / password:	admin / -
Web browser access ports:	80, 8000
PC client access ports:	8000
Mobile client access ports:	8000
RTSP URL:	<ul style="list-style-type: none"> <li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream</li> <li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream</li> </ul>
Alarm inputs / outputs:	4 / 1
PTZ control:	✓
Motion Detection:	22 x 18 motion zones
Intelligent Image Analysis:	✓
Mouse support:	✓
IR remote controller in the set:	✓
Switch PoE:	16-port PoE Switch built-in, 25.5 W / Channel - PoE (802.3af/at), max. 200 W (total)
Power supply:	100 ... 240 V AC @ 50 / 60 Hz
Weight:	2.56 kg
Dimensions:	380 x 325 x 52 mm
Supported languages:	English, Bulgarian, Croatian, Czech, Danish, Estonian, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Polish, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Country of origin:	China
Manufacturer / Brand:	Hikvision
SAP Code:	303602940
Guarantee:	<b>3 years</b>

## PRESENTATION

Front panel:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Rear panel:



In the kit:



## OUR OPINIONS



- Audio transmission via network.
- The DS-7616NI-12/16P is equipped with USB 3.0 port allowing to fast records backup.