

Code: BCS-P-NVR1602-4K-16

NVR **BCS-P-NVR1602-4K-16** P-II 16 CHANNELS +16-PORT SWITCH POE BCS POINT

Net: **597.86 EUR** Gross: **597.86 EUR**



SPECIFICATION

Standard:	TCP/IP
Supported resolutions:	max. 12 Mpx - 4000 x 3000 px
Video outputs:	• 1 pcs HDMI 4K • 1 pcs VGA
Audio support:	16 Channels - Audio from cameras
Audio inputs:	1 pcs CINCH - Microphone
Audio outputs:	1 pcs CINCH
Image compression method:	H.265 / Ultra H.265 / H.264 / MJPEG
Supported hard drives:	2 x 8 TB SATA
Recording modes:	Manual, Sensor, Motion detection, Schedule
Network protocols:	HTTP, HTTPS, TCP/IP, IPv4, UPnP, RTSP, RTP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, P2P
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow All channels synchronous playback, Smart Search function
Bitrate:	max. 480 Mbps (total)
Network functions:	Full support via network, Remote records copying, Web Server built-in max. 128 on-line users
Mobile phones support:	Port no.: 80 or access by a cloud (P2P) • Android: Free application BCS Point • iOS (iPhone): Free application BCS Point
Default IP address:	DHCP
Default admin user / password:	admin / 123456
Web browser access ports:	80, 554
PC client access ports:	80
Mobile client access ports:	80
RTSP URL:	rtsp://192.168.1.66:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.66:554/unicast/c1/s1/live - Sub stream

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Alarm inputs / outputs:	4 pcs / 1 pcs
USB:	• 1 pcs USB 2.0, • 1 pcs USB 3.0
PTZ control:	IP Speed Dome Cameras
Motion Detection:	22 x 18 motion zones, 6 sensitivity levels
Mouse support:	✓
IR remote controller in the set:	✓
Main features:	Fisheye-Dewarping - correction of the "fish eye" view to the perspective view
Switch PoE:	16-port PoE Switch built-in : • max. 30 W / Channel - PoE (802.3af/at) • max. 240 W (total) Cooperation with cameras with DHCP function activated
Power supply:	230 V AC
Weight:	2.53 kg
Dimensions:	380 x 325 x 50 mm, RACK 19", 1U
Supported languages:	Polish, English
Country of origin:	China
Manufacturer / Brand:	BCS POINT
Guarantee:	3 years

PRESENTATION

Front panel:



Rear panel:



In the kit:



OUR OPINIONS



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



- Audio transmission via network.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

