

Code: DS-7732NXI-I4/4S

IP DVR **DS-7732NXI-I4/4S** 32 CHANNELS ACUSENSE Hikvision

Net: **4 474.00 PLN** Gross: **5 503.02 PLN**

The DS-7732NXI-I4/4S digital recorder is a professional device using in IP surveillance systems. The H.265 / H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity.



SPECIFICATION

Standard:	TCP/IP
Supported resolutions:	max. 12 Mpx - 4000 x 3000 px
Video outputs:	1 pcs HDMI 4K 1 pcs HDMI 1 pcs VGA 1 pcs CVBS - BNC socket
Audio support:	32 Channels - Audio from cameras
Audio inputs:	1 pcs CINCH - External microphone input
Audio outputs:	1 pcs CINCH
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MPEG-4
Supported hard drives:	4 x 8 TB SATA + 1 x eSATA
Recording modes:	Manual, Sensor, Motion detection, Schedule
Network protocols:	TCP/IP, DHCP, DNS, DDNS, NTP, SADP, SMTP, NFS, HTTPS, UPnP, iSCSI, Hik Cloud P2P
External storage devices backup:	Backup to USB drive (pendrive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow
Bitrate:	max. 256 Mb/s
Network functions:	<ul style="list-style-type: none">• Live image view, Playback the records, Backup the records• max. 128 on-line users - iVMS-4200 application• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its
ONVIF:	
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) • Android: Darmowa aplikacja iVMS-4500 or Hik-Connect • iOS (iPhone): Darmowa aplikacja iVMS-4500 or Hik-Connect
Default admin user / password:	admin / -
Default IP address:	DHCP or 192.168.1.64
Web browser access ports:	80
PC client access ports:	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports:	8000

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

RTSP URL:	<ul style="list-style-type: none"> • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
Alarm inputs / outputs:	16 / 4
PTZ control:	<ul style="list-style-type: none"> • IP Speed Dome Cameras • RS-485 - PELCO-D/P and others
Motion Detection:	<input type="checkbox"/>
Intelligent Image Analysis:	<input type="checkbox"/>
Main features:	<ul style="list-style-type: none"> • NVR from the AcuSense series • Filtering of false alarms based on recognition of persons and vehicles (line crossing, intrusion) - max. 4 Mpx
USB:	1 pcs USB 3.0 2 pcs USB 2.0
Mouse support:	<input type="checkbox"/>
IR remote controller in the set:	<input type="checkbox"/>
Power supply:	100 ... 240 V AC
Operation temp:	-10 °C ... 55 °C
Weight:	4.3 kg
Dimensions:	445 x 400 x 75 mm, RACK 19", 1.5U
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Country of origin:	China
Manufacturer / Brand:	Hikvision
SAP Code:	303607714
Guarantee:	3 years

PRESENTATION

Front panel:



Rear panel:



See how to mount a hard disk drive and configure the recorder:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

In the kit:



OUR OPINIONS



- Audio transmission via network.
- The DS-7732NXI-I4/4S is equipped with USB 3.0 port allowing to fast records backup.

