

Code: APTI-N6418-4KS3

NVR **APTI-N6418-4KS3** 64 CHANNELS

Net: **543.31 EUR** Gross: **668.27 EUR**

The APTI-N6418-4KS3 digital recorder is a professional device using in IP surveillance systems. The H.265 / H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.

Attention! To use the full functionality of the recorder we recommend using the APTI cameras.



SPECIFICATION

| | |
|-------------------------------------|--|
| Standard: | TCP/IP |
| Supported resolutions: | max. 8.8 Mpx - 4096 x 2160 px - Supports up to 35 cameras max. 5 Mpx - Supports up to 58 cameras max. 4 Mpx - Supports up to 64 cameras |
| Video outputs: | 1 pcs HDMI 4K 1 pcs VGA 1 pcs HDMI - SPOT max. 32 cameras |
| Audio support: | 64 Channels - Audio from cameras |
| Audio inputs: | 1 pcs CINCH |
| Audio outputs: | 1 pcs CINCH |
| Image compression method: | H.265+ / H.265 / H.264+ / H.264 |
| USB: | 2 pcs USB 2.0 1 pcs USB 3.0 |
| Supported hard drives: | 8 x 6 TB SATA + 1 x eSATA |
| Recording modes: | Manual, Motion Detection, Schedule |
| Network protocols: | TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP, P2P, ONVIF 2.4, Private |
| External storage devices backup: | Records backup at (.avi) format to USB (pendrive) |
| Searching and playback the records: | Records searching: timeline or file list. Playback: forward, fast Playback the records : 4 @ 3840 x 2160, 25 fps 6 @ 2592 x 1944, 25 fps 8 @ 2688 x 1520, 25 fps 10 @ 2048 x 1536, 25 fps 16 @ 1920 x 1080, 25 fps |
| Bitrate: | 350 Mbps |
| Network functions: | Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters |
| Operation temp: | -10 °C ... 55 °C |
| ONVIF: | ✓ |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

| | |
|----------------------------------|--|
| Mobile phones support: | Port no.: 6000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision, Android: Free application iVMS320 • iOS (iPhone): Free application BitVision, iOS: Free application iVMS320 |
| Default IP address: | 192.168.1.88 |
| Default admin user / password: | admin / 12345 |
| Web browser access ports: | 80, 5000, 554 |
| PC client access ports: | 80, 5000, 554 |
| Mobile client access ports: | 80, 5000, 6000 |
| Alarm inputs / outputs: | — |
| PTZ control: | IP Speed Dome Cameras |
| Motion Detection: | Split the screen into zones : 24 x 18 motion zones |
| Mouse support: | ✓ |
| IR remote controller in the set: | — |
| Power supply: | 230 V AC |
| Weight: | 7.2 kg |
| Dimensions: | 440 x 445 x 100 mm - Rack 19" |
| Supported languages: | Polish, English, Bulgarian, Czech, French, Spanish, German, Portuguese, Russian, Turkish, Hungarian, Italian |
| Country of origin: | China |
| Manufacturer / Brand: | APTI |
| Guarantee: | 2 years |

PRESENTATION

Front panel:



Rear panel:



See how to mount a hard disk drive and configure the recorder:

:

In the kit:





OUR OPINIONS



- The APTI-N6418-4KS3 is equipped with USB 3.0 port allowing to fast records backup.

PACKAGE

| | |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|

