

Code: NVR724-256

NVR **NVR724-256** 256 CHANNELS +eSATA DAHUA

Net: **1 108.88 EUR** Gross: **1 108.88 EUR**



SPECIFICATION

Standard:	TCP/IP
Supported resolutions:	max. 12 Mpx - 4000 x 3000 px
Video outputs:	2 pcs HDMI 1 pcs VGA
Audio support:	256 Channels - Audio from cameras
Audio inputs:	1 pcs Jack 3.5 mm socket - Microphone
Audio outputs:	1 pcs - Jack 3.5 mm socket
Image compression method:	H.264 / MJPEG
Supported hard drives:	24 x 8 TB SATA III + 1 x eSATA Operation modes : SINGLE, RAID 0/1/5/6/10/50/60
Recording modes:	Manual, Sensor, Motion detection, Schedule
Network protocols:	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP ONVIF 2.4
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow "Frame by Frame" playback function
Bitrate:	max. 512 Mbps (total)
Network functions:	Full support via network, Remote records copying, Web Server built-in max. 128 on-line users
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application
Default IP address:	192.168.1.108
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80, 37777




PC client access ports:	37777
Mobile client access ports:	37777
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Alarm inputs / outputs:	4 pcs / 4 pcs
PTZ control:	✓
Motion Detection:	22 x 18 motion zones
USB:	2 pcs USB 2.0 2 pcs USB 3.0
Intelligent Image Analysis:	✓
Mouse support:	✓
IR remote controller in the set:	—
Main features:	• Ability to work drives in a RAID array can significantly improve system reliability • Used in the construction holders (24 pcs) allow for quick and easy replacement of any of the hard drives • Bi-directional audio streaming support
Power supply:	100 V ... 240 V AC
Power consumption:	≤ 200 W (without HDD)
Weight:	24.5 kg (without HDD)
Dimensions:	545 x 485 x 175 mm - RACK 19" 4U
Supported languages:	Polish, English
Country of origin:	China
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION

Front panel:



Used in the construction holders (24 pcs) allow for quick and easy replacement of any of the hard drives:





Rear panel:



In the kit:



Example captures of device interface:



OUR OPINIONS



- Audio transmission via network.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------