

Code: NVR608-128-4KS2

IP DVR **NVR608-128-4KS2** 128 CHANNELS +eSATA DAHUA

Net: **2 494.57 EUR** Gross: **3 068.32 EUR**



SPECIFICATION

Standard:	TCP/IP
Supported resolutions:	max. 12 Mpx @ 4000 x 3000 px
Video outputs:	2 pcs HDMI 4K 1 pcs VGA
Audio support:	128 Channels - Audio from cameras
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MPEG-4 / MJPEG
Supported hard drives:	8 x 10 TB SATA III + 1 x eSATA Operation modes : SINGLE, Raid 0/1/5/6/10
Recording modes:	Manual, Sensor, Motion detection, Schedule
Network protocols:	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search, P2P, ONVIF
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow "Frame by Frame" playback function Records playback from max. 16 channels in the same time @ 1080p, 30 fps
Bitrate:	max. 384 Mbps (total)
Network functions:	<ul style="list-style-type: none">• 2 x Port Ethernet 10/100/1000 Mb/s• Full support via network, Remote records copying, Web Server built-in
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application DMSS• iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application
Default IP address:	192.168.1.108
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80, 37777

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

PC client access ports:	37777
Mobile client access ports:	37777
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Alarm inputs / outputs:	16 pcs / 8 pcs
PTZ control:	RS-485, Many protocols
USB:	2 pcs USB 2.0 2 pcs USB 3.0
RS-232 interface:	✓
Motion Detection:	✓
Intelligent Image Analysis:	✓
Mouse support:	✓
IR remote controller in the set:	—
Main features:	<ul style="list-style-type: none"> • Ability to work drives in a RAID array can significantly improve system reliability <p>Functions are realized in cooperation of the recorder with cameras that support these functions :</p> <ul style="list-style-type: none"> • ANPR - License plate recognition • SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle • Face recognition - supports 6 types of facial attributes extraction • crossing the line (tripwire) • intrusion • counting people in a given area • crowd gathering estimation • Heat map - the selection in the image by corresponding colors the areas with different traffic
Power supply:	100 V ... 240 V AC
Power consumption:	≤ 20 W (without HDD)
Weight:	9 kg (without HDD)
Dimensions:	444 x 459 x 95 mm
Supported languages:	Polish, English
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION

View after open the front cover:



Front panel:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60




Rear panel:



In the kit:



Example captures of device interface:





OUR OPINIONS



- Audio transmission via network.
- The NVR608-128-4KS2 is equipped with USB 3.0 port allowing to fast records backup.

