

Code: DS-7732NI-K4/16P

## IP DVR **DS-7732NI-K4/16P** 16 CHANNELS, 16 PoE Hikvision

Net: **4 415.00 PLN** Gross: **5 430.45 PLN**

The DS-7732NI-K4/16P digital recorder is a professional device using in IP surveillance systems. The H.265 / H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity.



### SPECIFICATION

|                                     |   |
|-------------------------------------|---|
| Standard:                           | TCP/IP  |
| Supported resolutions:              | max. 8.3 Mpx 4K UHD - 3840 x 2160 px  |
| Video outputs:                      | 1 pcs HDMI 4K<br>1 pcs VGA<br>There is a possibility to configure a SPOT function on one of the output  |
| Audio support:                      | 32 Channels - Audio from cameras  |
| Audio inputs:                       | 1 pcs CINCH   |
| Audio outputs:                      | 1 pcs CINCH   |
| Image compression method:           | H.265+ / H.265 / H.264+ / H.264 / MPEG-4  |
| Supported hard drives:              | 4 x 8 TB SATA   |
| Recording modes:                    | Manual, Sensor, Motion detection, Schedule  |
| Network protocols:                  | TCP/IP, DHCP, IPv4/IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS  |
| External storage devices backup:    | Backup to USB drive (pendrive, external drive)  |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow<br>Records playback from max. 16 channels in the same time  |
| Bitrate:                            | max. 256 Mbps   |
| Network interface:                  | 10/100/1000 Mbps  |
| Network functions:                  | <ul style="list-style-type: none"><li>• Live image view, Playback the records, Backup the records</li><li>• max. 128 on-line users - iVMS-4200 application</li></ul>  |
| ONVIF:                              | ✓   |
| Mobile phones support:              | Port no.: 8000 or access by a cloud (P2P)<br><ul style="list-style-type: none"><li>• Android: Free application <a href="#">Hik-Connect</a></li><li>• iOS (iPhone): Free application <a href="#">Hik-Connect</a></li></ul> |
| Default IP address:                 | DHCP or 192.168.1.64  |
| Default admin user / password:      | admin / -   |
| Web browser access ports:           | 80  |
| PC client access ports:             | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application   |
| Mobile client access ports:         | 8000  |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|                                  |  |
|----------------------------------|--|
| RTSP URL:                        | <ul style="list-style-type: none"> <li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream</li> <li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream</li> </ul>  |
| Alarm inputs / outputs:          | 16 / 4   |
| PTZ control:                     | <ul style="list-style-type: none"> <li>• IP Speed Dome Cameras</li> <li>• RS-485 - PELCO-D/P and others</li> </ul>   |
| Motion Detection:                | ✓  |
| Intelligent Image Analysis:      | ✓  |
| Main features:                   | <p>Functions are realized in cooperation of the recorder with cameras that support these functions</p> <ul style="list-style-type: none"> <li>• crossing the line (tripwire)</li> <li>• intrusion</li> <li>• people counting</li> <li>• heat map</li> <li>• ANPR - License plate recognition</li> </ul> <ul style="list-style-type: none"> <li>• RS-232 interface</li> </ul> |
| USB:                             | 1 pcs USB 3.0<br>2 pcs USB 2.0   |
| Mouse support:                   | ✓  |
| IR remote controller in the set: | ✓  |
| Switch PoE:                      | 16-port PoE Switch built-in, 25.5 W / Channel - PoE (802.3af/at) max. 200 W (total)  |
| Operation temp:                  | -10 °C ... 55 °C   |
| Power supply:                    | 100 ... 240 V AC   |
| Weight:                          | 4.58 kg  |
| Dimensions:                      | 440 x 400 x 75 mm  |
| Supported languages:             | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian  |
| Country of origin:               | China  |
| Manufacturer / Brand:            | Hikvision  |
| SAP Code:                        | 303603712  |
| Guarantee:                       | <b>3 years</b>   |

## PRESENTATION

Front panel:



Rear panel:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
 POL; 60-713 Poznań; Graniczna 10  
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

See how to mount a hard disk drive and configure the recorder:

:

In the kit:



## OUR OPINIONS



- The DS-7732NI-K4/16P is equipped with USB 3.0 port allowing to fast records backup.

## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60