

Code: DS-PM-WO2

WIRELESS EXPANDER **DS-PM-WO2** Hikvision

Net: **61.98 EUR** Gross: **61.98 EUR**

The DS-PM-WO2 device is equipped with two NO/NC relay outputs managed wirelessly from the alarm control panel.



SPECIFICATION

Support:	Hikvision
Number of outputs:	2 pcs - programmable
Outputs type:	2 pcs NO/NC - Relay
Relay switching voltage:	max. 30 V DC
Relay switching current:	max. 1 A DC
Frequency band:	868 MHz
Transmission speed:	10 kbps
Radio communication range (at open area):	800 m (open area)
Tamper protection:	Tamper protection (detection of removing from mounting surface and enclosure opening)
Main features:	• Bi-directional encrypted radio communication • AES-128 data encryption • Intelligent jamming detection • Operation status LED indicator : Red / Green
Power supply:	9 ... 15 V DC (power adapter included)
Operation temp:	-10 °C ... 55 °C
Weight:	0.17 kg
Dimensions:	162 x 105 x 29 mm
Manufacturer / Brand:	Hikvision
SAP Code:	302401257

Guarantee:

2 years

PRESENTATION

Front panel:



Internal view of the housing:



Mounting side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------