
Code: JA-151N

PG WIRELESS OUTPUT MODULE **JA-151N** JABLOTRON

Price visible after login

The PG wireless output module does not occupy a specific address in the system. The device has one switchable relay output 1A/24V DC (C, NO, NC) which, depending on the settings of switches is assigned to 1 of 32 PG outputs of the control unit.



SPECIFICATION

Support:	JABLOTRON 100
Power supply:	12 V ... 24 V DC
Relay contacts rating (resistive load):	1 A / 30 V AC
Environment class:	II indoor area according to EN 50131-1, EN 50131-3
Operation temp:	-10 ... 40 °C
Weight:	0.024 kg
Dimensions:	83 x 50 mm - PCB
Manufacturer / Brand:	JABLOTRON
Guarantee:	2 years


PRESENTATION

Connectors:



Top view:

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60