Code: BNC-W/4781G-MTC*P10

COMPRESSION PLUG **BNC-W/4781G-MTC*P10** RG6 Triset113 METACON

Net: 2.01 EUR Gross: 2.01 EUR



BNC plug crimped on coaxial cable.
The kind of material used eliminates any corrosion. High precision ensures low loss and insertion force, as well as nice look. It can be compressed with ease, providing stable high performance connectivity for a long time.
The connector is produced under strict technological discipline. The plug is tight in the socket, there is no risk of loosing the contact, which takes place in the case of cheap connectors. The inner conductor of the cable inserted into the inlet is centered and stopped.

METACON - leading manufacturer of connectors.

SPECIFICATION

In package:	**10 pcs The price for package**
Connector type:	BNC Plug
Attachment of connector elements:	Compression mounting
Application:	Coaxial cable
Dielectric diameter:	max. 4.7 mm
Wire mounting:	Pressing
Cable diameter:	max. 8.1 mm
Shield fastening:	Compression mounting
Watertightness:	✔
Example of application:	• RG6 • HFEK • Triset113
Main features:	• Properly compressed connection is highly resistant to break • Watertightness of connector with cable connection • Very easy and quick assembly • Corrosion resistance • Very low loss in the whole operating band • To crimp use the crimping tool HT-5082R
Weight:	0.160 kg
Dimensions:	Ø 15 x 41 mm
Manufacturer / Brand:	METACON
Guarantee:	2 years

PRESENTATION

Connector view from cable assembly side:

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60





Terminating of BNC compression connectors using a compression tool:
:

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg