

Code: BNC-W/3770

COMPRESSION PLUG **BNC-W/3770** RG59 YAP

Net: **0.48 EUR** Gross: **0.48 EUR**

BNC plug crimped on coaxial cable.

The kind of material used eliminates any corrosion. High precision ensures low loss and insertion force, as well as nice look. It can be compressed with ease, providing stable high performance connectivity for a long time.

The connector is produced under strict technological discipline. The plug is tight in the socket, there is no risk of losing the contact, which takes place in the case of cheap connectors. The inner conductor of the cable inserted into the inlet is centered and stopped.



SPECIFICATION

Connector type:	BNC Plug
Attachment of connector elements:	Compression mounting
Application:	Coaxial cable
Dielectric diameter:	max. 3.7 mm
Wire mounting:	Pressing
Cable diameter:	max. 7.3 mm
Shield fastening:	Compression mounting
Watertightness:	✓
Example of application:	<ul style="list-style-type: none">• RG59• YAP• K-60
Main features:	<ul style="list-style-type: none">• Properly compressed connection is highly resistant to break• Watertightness of connector with cable connection• Very easy and quick assembly• Corrosion resistance• Very low loss in the whole operating band• To crimp use the crimping tool HTL-548 / HT-5082R
Weight:	0.012 kg
Dimensions:	Ø 14.5 x 39 mm
Guarantee:	2 years

PRESENTATION

Connector view from cable assembly side:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Attention! Depend on delivery, the product is available in different variants (it is not subject to selection):



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

