

Code: BNC-WK/ZAC-RG6

ANGULAR COMPRESSION PLUG **BNC-WK/ZAC-RG6**

Net: **0.91 EUR** Gross: **1.12 EUR**

The connector is equipped with a plastic bush, which during compression of the connector is tightly pressed against the sheath of the cable (by putting on cone brass case - the compression ring). The BNC-WK/ZAC-RG6 professional compression connector fulfills all recommendations of SCTE (The Society of Cable Telecommunications Engineers) for this kind connectors.

The features of the connector have been specially matched to the RG-6 cables. The dimensions are so matched that after compression connector is crimped on the cable sheath with a force so large that break the connector from the cable is impossible and so small that it does not damage the structure of the cable.



SPECIFICATION

Connector type:	BNC Angular plug
Attachment of connector elements:	Compression mounting
Impedance:	75 Ω
Material:	Brass (Nickel-plated)
Application:	Coaxial cable
Dielectric diameter:	max. 6.3 mm
Wire mounting:	Pressing
Cable diameter:	max. 8.5 mm
Shield fastening:	Compression mounting
Watertightness:	✓
Example of application:	RG6
Main features:	<ul style="list-style-type: none">• Wide frequency range• Very low loss in the whole operating band• Perfect matching to the transmission line within the whole operating band• Watertightness of connector with cable connection• Resistance to corrosion - made of non-ferrous metals and highest-quality dielectric• Properly compressed connection is highly resistant to break• Many patent-pending solutions• To crimp use the crimping tool ZAC/MSR-2K, HT-5082R
Weight:	0.024 kg
Dimensions:	14.5 x 40 x 28 mm
Guarantee:	2 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

