

Code: DS-PWA32-H

WIRELESS ALARM CONTROL PANEL **DS-PWA32-H** Hikvision

Net: **138.73 EUR** Gross: **170.64 EUR**

The DS-PWA32-H wireless alarm control panel supports 32 wireless alarm inputs and 32 wireless outputs. In addition, the device allows to handle max. 2 wireless sirens and up to 8 remote controls.



SPECIFICATION

Number of supported wireless detectors:	max. 32 pcs
Number of supported remote control keyfobs:	max. 8 pcs
The RFID cards/keyfobs support:	—
Number of supported wireless sirens:	max. 2 pcs
Operating frequency range of the wireless devices:	868 MHz
Operating range in open area:	max. 800 m
Partitions:	1 pcs
Timers:	—
Users + admins:	11 + 2
Keyboard included:	—
Expander included :	—
Built-in modules:	<ul style="list-style-type: none">• Wi-Fi Module IEEE 802.11 b/g/n, 2.4 GHz• LAN, 10/100Mb
Access from PC:	iVMS-4200 application
Mobile phones support:	✓
Power supply:	5 V DC / 2 A (power adapter included)
Main features:	<ul style="list-style-type: none">• Support for bidirectional communication of alarm events and other signals via the LAN, Wi-Fi networks using the main and backup channels• Support for video events via a mobile client and email• Configuration via the www client, mobile client or software• Compliance with the SIA-Contact ID protocol• Speaker built-in• Emergency Power Supply : built-in battery Li-Ion 3.8 V / 4520 mAh - 17.176 Wh
Housing:	Plastic
Color:	White
Operation temp:	-10 °C ... 55 °C
Dimensions:	155 x 155 x 35 mm

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Manufacturer / Brand:	Hikvision
SAP Code:	302401100
Guarantee:	3 years

PRESENTATION

Top view:



Bottom view:



Connectors:



In the kit:

