

Code: INT-KWRL2-SSW

WIRELESS KEYBOARD WITH RFID INT-KWRL2-SSW ABAX/ABAX2 SATEL

Net: 168.35 EUR Gross: 207.07 EUR



The device is designed to work within two-way wireless ABAX/ABAX2 system.

The INT-KWRL2-SSW keypad is intended for daily operations and programming the Integra series alarm control system. With the LCD display showing text messages, even advanced functionalities of the alarm control unit are simple and convenient.

The built-in proximity card reader allows to operate the system without the necessity to remember passwords.

Keypad is powered by battery (included) and communicates with alarm control panel using a special radio transmission protocol (bidirectional communication).

SPECIFICATION

Support:	ABAX/ABAX2
Frequency band:	868 MHz ... 868.6 MHz
Radio communication range (at open area):	<ul style="list-style-type: none">• ≤ 800 m - ABAX2 @ ACU-220,• ≤ 800 m - ABAX2 @ ACU-280,• ≤ 800 m - ABAX @ ACU-120,• ≤ 400 m - ABAX @ ACU-270
Main features:	<ul style="list-style-type: none">• proximity reader built-in• Large, easily readable LCD with backlight displaying detailed information on system state• Operation status LED indicator• Alarms: keypad hold-down PANIC, FIRE and AUX• Buzzer for acoustic signaling of some system events• Microswitch as tamper contact
Power supply:	2 x CR123A (included)
Color:	Silver
Operation temp:	-10 °C ... 55 °C
Weight:	0.34 kg
Dimensions:	145 x 143 x 25 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years

PRESENTATION


DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



View after open the front cover:



Internal view of the housing:



Mounting side view:



In the kit:

