

Code: XD-2-BR

MULTIPURPOSE WIRED DETECTOR **XD-2-BR** SATEL

Net: **21.31 EUR** Gross: **26.21 EUR**

The XD-2-BR wired detector can work in one of the 4 modes, which makes it an extremely universal device. Depending on your needs, the device can be configured as: magnetic detector, shock detector, shock detector with reed switch or water flood detector (FPX-1 external probe required - available separately).

The XD-2-BR works with any alarm control panel.



SPECIFICATION

| | |
|---|---|
| Support: | Alarm control panel |
| Detection: | Opening the door or window, Vibrations, Water |
| Environmental class EN 50130-5: | II |
| Protection class (Grade): | 2 |
| Sensitivity adjustment: | — |
| Alarm signaling: | LED indicator, Signal to control panel |
| Relay contacts rating (resistive load): | 40 mA / 24 V DC |
| Power supply: | 12 V DC / 14 mA (max) |

| | |
|-----------------------|--|
| Main features: | <ul style="list-style-type: none"> • Operation modes : <ul style="list-style-type: none"> - Magnetic detector - Opening the door or window - input for connecting a NC type wired detector - 1 Alarm output <ul style="list-style-type: none"> - Shock detector - Detection of shocks and vibrations associated with attempts to force a door or window - Range : 3 m - input for connecting a NC type wired detector - 1 Alarm output <ul style="list-style-type: none"> - Shock and magnetic detector - Detection of shocks and vibrations associated with attempts to force a door or window - Opening the door or window - input for connecting a NC type wired detector - 2 Alarm outputs <ul style="list-style-type: none"> - Water flood detector - The required FPX-1 probe is available separately - detecting the presence of water in spaces where there is a risk of leakage - 1 Alarm output • Tamper detection - opening the enclosure, removing from mounting surface • LED indication • Supply voltage control • 2 magnets included (for surface and flush mounting) • Compliance to EN 50130-4, EN 50130-5, EN 50131-1, EN 50131-2-6 standards |
| Color: | Brown |
| Operation temp: | -10 °C ... 55 °C |
| Weight: | 0.023 kg |
| Dimensions: | <ul style="list-style-type: none"> • 20 x 102 x 23 mm (detector) • Ø 10 x 28 mm (magnet) |
| Manufacturer / Brand: | SATEL |
| Guarantee: | 2 years |

PRESENTATION

Front view:



Internal view of the housing:



Mounting side view:



In the kit:

