Code: AGD-200-BR

# WIRELESS GLASS BREAK DETECTOR **AGD-200-BR** SATEL

Net: 58.65 EUR Gross: 58.65 EUR



Sensor signals an alarm on registering a low-frequency tone (impact sound), followed by a high-frequency tone (sound of broken glass). The sensor starts to analyze a high-frequency channel after receiving the low-frequency sound wave, caused by the impact.
The AGD-200-BR supports the other devices copmpatible with wireless ABAX/ABAX2 system.


**SPECIFICATION**

| | |
|---|---|
| Detection: | detection of breaking plate, laminated or tempered glass |
| Support: | Satel ABAX/ABAX2 |
| Alarm signaling: | Signal to control panel |
| Frequency band: | 868 MHz ... 868.6 MHz |
| Radio communication range (at open area): | ~ 500 m @ ABAX ,<br>~ 2000 m @ ABAX2 |
| Battery: | CR123A 3 V - 3.0 V (included) |
| Backup time: | ~ 2 years |
| Main features: | • advanced dual-path microprocessor signal analysis<br>• Remote configuration<br>• Tamper protections |
| Operation temp: | -10 °C ... 55 °C |
| Color: | Brown |
| Weight: | 0.02 kg |
| Dimensions: | 20 x 102 x 23 mm |
| Manufacturer / Brand: | SATEL |
| Guarantee: | 2 years |

**PRESENTATION**

Internal view of the housing:

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60




Mounting side view:




In the kit:



**PACKAGE**

| | |
|---|---|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60